# Eaton 8D0C19TT32SC

Catalog Number: 8D0C19TT32SC

Titanium square flange receptacle, no plating, with female short PCB contacts, keying C; 8D0C19TT32SC

## General specifications



Product Name

Eaton Souriau 8D PCB series MIL-DTL- 8D0C19TT32SC

38999 series III PC tail version

connectors

Product Length/Depth

Catalog Number

34.1 mm

**Product Height** 

36 mm

**Product Width** 

36 mm

**Product Weight** 

67 g



## Product specifications

Connector orientation

Fitted with: Shielding

С

## Resources

Connector type
Contact delivery
Loaded
Contact gender Socket (Female)
Contact type
Contact type  Coupling type
Degree of protection
IP67
Layout
32
Plating
Nickel
Shell material
Shell size 19
Mating cycles 500
Operating temperature - max
200 °C
Operating temperature - min
-65 °C
Receptacle type Square Flange Receptacle
Number Of Contacts 32
Number of cavity #20
32
PCB diameter
0.5 mm

#### Salt spray

500 hour

Working voltage (Vrms)

1800 V



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia