

Eaton 8D0C25M37SD

Catalog Number: 8D0C25M37SD

Composite square flange receptacle, Nickel plating, with female short PCB contacts, keying D; 8D0C25M37SD

General specifications



| Product Name | Catalog Number |
|--|----------------|
| Eaton Souriau 8D PCB series MIL-DTL- 38999 series III PC tail version connectors | 8D0C25M37SD |
| Product Length/Depth | 36.01 mm |
| Product Height | Product Width |
| 46 mm | 46 mm |
| Product Weight | |
| 91 g | |

Product specifications

Resources

Fitted with:

Shielding

Connector orientation

D

Connector type

Contact delivery

Loaded

Contact gender

Socket (Female)

Contact plating

Contact type

Coupling type

Degree of protection

IP67

Layout

37

Plating

Nickel

Shell material

Shell size

25

Mating cycles

500

Operating temperature - max

200 °C

Operating temperature - min

-65 °C

Receptacle type

Square Flange Receptacle

Number Of Contacts

37

Number of cavity #16

37

PCB diameter

0.5 mm

Salt spray

2000 hour

Working voltage (Vrms)

2300 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)