



USB_A PLUG CONTACT NO.	WIRE COLOUR	4 Pins Conn. CONTACT NO.	Ground Wire
1	RED	1	/
2	WHITE	2	/
3	GREEN	3	/
4	BLACK	4	/
SHELL	BRAID	/	1

- Notes:
1. CABLE:2C 28AWG+2C 24 AWG USB CABLE OD=4.0±0.2MM
 2. ELECTRICAL TEST :CT:2.0 Ohm ,IS:10M Ohm ,DC 250V
 3. FLEXIBLE TEST:NO OPEN AND SHORT
ANGLE:±60° WEIGHT:500g
SPEED:30CPM TOTAL CYCLES:2000
 4. CABLE ASSY MUST BE 100% TESTED FOR OPEN,SHORT,MISWIRE.
 5. THE PRODUCT SHOULD BE FINISHED WITH THE CAP(COMPONENT No.14) COVERED
 6. DIMENSION MARKED SHOULD BE CHECKED BY Q.C. AND PROCESS ENGINEERS.
 7. PLEASE CONTACT FOXCONN SALES REPRESENTATIVE TO VERIFY PRODUCT DETAIL&AVAILABILITY

14	CORE OVERMOLD	A/R	TBD	PVC 65P,COLOR: WHITE
13	CAP	1	TBD	PE
12	CORE	A/R	020-0020-629	RH 4*5*2MM
11	SR OVERMOLD	A/R	TBD	PVC 40P,COLOR: WHITE
10	OVERMOLD	A/R	TBD	PVC 65P,COLOR: WHITE
9	INNER MOLD	A/R	901-0103-008	LOW PE
8	H.S. TUBE	A/R	080-S039-620	S901 BLACK ID=1.5mm
7	H.S. TUBE	A/R	080-2006-620	SUMITUBE:F32-4 BLACK ID=5.0
6	CORE	1	020-0021-629	RH 9.8*19*4.9
5	RAW CABLE	A/R	TBD	SHOW AS NOTES.1
4	TERMINIAL	4	TBD	TBD
3	4 PIN CONN.	1	TBD	TBD
2	TOP SHELL	1	025-0302-455	MATERIAL:SP3CC FINISH:CU:120V*MMI NICKEL:100-200V
1	USB_A PLUG	1	UB2010C-SP1-4F	COLOR:BLACK(PBT),WITHOUT MARK
No.	DESCRIPTION	Q'TY	FOXCONN P/N	REMARKS
X.±	X.±	UNITS	NAME:(INTENDED USE)	FOXCONN
X.± 5	X.±	MAT'L	CUSTOMER	HON HAI PRECISION IND. CO.,LTD. TAIPEI, TAIWAN, R.O.C.
X.X±	X.X±	FINISH	PART NO.(INTENDED USE)	TITLE: USB A plug to 4pin conn.
XXXX±	XXXX±		CUBD005P-S47-EF	DWG NO.: 605-0000-2945
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON HAI PRECISION IND. CO.,LTD. NO. PARTS OR INFORMATION SHOULD BE LOANED, COPIED, REPRODUCED, OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON HAI PRECISION IND. CO., LTD.			APPD: Y.M. Her 08/16/07	SCALE SHEET REV. X4
			CHKD: Joe J.F.Chien 08/16/07	SCALE SHEET REV. X4
			DR: Yonghong Chang 08/15/07	SCALE SHEET REV. X4