

PRODUCT-DETAILS

General Information

11120406/44BT XTE9200S-M3/BT



Extended Product Type	11120406/44BT
Product ID	7TCA305020R0321
EAN	8713812777160
Catalog Description	XTE9200S-M3/BT
Long Description	Self-contained 4 watt maintained surface mount led luminaire, including control module, series Indulux wireless - bluetooth
Technical	
Function	Escape route lighting/signage
Rated Voltage (U _r)	220230 V
Input Voltage Type	AC
	3.5 W
Power Supply Type	Peripheral (Individual Battery)
Number of Poles	4
Number of Lamps	1
Number of Lighting Heads	1
Functional Testing Capability	Safety Module for Monitoring (Central Feeded System)
Wiring Configuration	Continuous circuit/emergency circuit Suitable for through wiring
Ballast Type	Current Controlled

11120406/44BT 2

Lamp Type LED not exchangeable Marking Type Marking Type InsertSheet Mounting Type Wall surface mounted / celling surface mounted / period for Single-stated (Cover Material Pleaste, Transparent Housing Material Statement Statement (Cover Material Pleaste, Transparent Housing Material Statement (Cover Material Pleaste, Transparent Housing Color Statement (Cover Material Pleaste) (Cover Material Ple	Connection Type	Pluggable
Plate	•	LED not exchangeable
Mounting Type Wall surface mounted / celling surface mounting Type of Indicator Single-sided Single-sided Cover Material Pleasit, Transpared Cover Material Stainless steel Illuminance 200 Immodified Housing Cofor Stainless Steel Illuminance 100 Immodified Battery Chemical Nickel-Metal Hydride Composition Nickel-Metal Hydride Ambient Yeight 200 go Number of Batteries 1 Environmental 6000 K Environmental Product Net Fight Product Net Class Isolated Class III Dimensions Insolated Class III Product Net Wildth 114 mm Product Net Weight 10 mm Product Net Weight 10 mm Product Net Weight 1 piece Product Net Weight 1 piece Package Level 1 Units box 1 piece Package Level 1 Gross 2 220 kg Weight 9 AKK 108468A7088 Installation Instructions and Manuals 9 AKK 107892A883 Popular Downloads 11124069448T	Marking Type	InsertSheet
Cover Material Plastic, Transparent Housing Material Stainless state Illuminance 200 Im Housing Color Stainless Steel Battery Chemical Nickel-Metal Hydride Composition Industrial Battery Type Industrial Statery Weight 200 g Number of Batteries 1 Environmental 6000 K Environmental 1 Ambient Temperature 0 - 40 °C Degree of Protection 1888 Protection Class Isolated (Class II) Dimensions 114 mm Product Net Net Weight 114 mm Product Net Height 114 mm Product Net Weight 1,945 kg Ordering Minimum Order Quantity 1 piece Product Net Weight 1,945 kg Ordering Minimum Order Quantity 1 piece Package Level 1 Units box 1 piece Package Level 1 Gross 2,220 kg Weight 9AKK108468A7088 Certificates and Declarations	Mounting Type	Wall surface mounted / ceiling surface mounting
Housing Material Stainless steet Illuminance 200 tm University Stainless Steet Battery Chemical Nicket-Metal Hydride Composition Nicket-Metal Hydride Nicket-Meta	Type of Indicator	Single-sided
Illuminance	Cover Material	Plastic, Transparent
Housing Color Stainless Staet Battery Chemical Nickel-Metal Hydride Composition Compos	Housing Material	Stainless steel
Battery Chemical Composition Nickel-Metal Hydride Composition Battery Type Industrial Battery Weight Battery Weight 200 g Number of Batteries Interval of Batteries 1 Environmental 6000 K Environmental Protection Ambient Temperature 0 _ 40 °C Degree of Protection IP68 Protection Class Isolated (Class II) Dimensions Interval of the Weight of the Medical Hydrogen Acceptable	Illuminance	200 lm
Composition Industrial Battery Type Industrial Sattery Weight 200 g Number of Batteries 1 Environmental 6000 K Environmental -40°C Degree of Protection 1988 Protection Class Isolated (Class II) Dimensions Product Net Width 114 mm Product Net Height 114 mm Product Net Depth / 400 mm Length 1,945 kg Ordering Minimum Order Quantity 1 piece Package Level 1 Units bot 1 piece Package Level 1 Gross 2,220 kg Weight -Certificates and Declarations Declaration of Conformity 9AKK108468A7088 Installation -Certificates and Manuals 9AKK107992A6837 Popular Downloads	Housing Color	Stainless Steel
Battery Weight 200 g Number of Batteries 1 60000 K 60000 K Environmental - 40 °C Degree of Protection 1P88 Protection Class Isolated (Class II) Dimensions - 114 mm Product Net Weight 114 mm Product Net Depth / Length 400 mm Length 1.945 kg Ordering - 1.945 kg Ordering - 220 kg Minimum Order Quantity 1 piece Package Level 1 Units box 1 piece Weight - 2220 kg Weight - 2220 kg Installation - 1.945 kg Popular Downloads - 240 kg Data Sheet, Technical 11120406/4458T		Nickel-Metal Hydride
Number of Batteries 1 Environmental 6000 K Ambient Temperature 0 - 40 °C Degree of Protection IP68 Protection Class Isolated (Class II) Dimensions Product Net Width 114 mm Product Net Height 114 mm Product Net Weight 400 mm Length 400 mm Product Net Weight 1.945 kg Ordering Minimum Order Quantity 1 piece Package Level 1 Units box 1 piece Package Level 1 Gross 2.220 kg Weight 9AKK108468A7088 Certificates and Declarations 9AKK108468A7088 Installation Instructions and Manuals 9AKK107992A6837 Popular Downloads Data Sheet, Technical 111204064448T	Battery Type	Industrial
Environmental	Battery Weight	200 g
Environmental Ambient Temperature 0.40°C Degree of Protection IP68 Protection Class Isolated (Class II) Dimensions Product Net Width 114 mm Product Net Height 114 mm Product Net Depth / 400 mm Length 1970	Number of Batteries	1 6000 K
Ambient Temperature 0 _ 40 ^ C Degree of Protection IP68 Protection Class Isolated (Class II) Dimensions Product Net Width 114 mm Product Net Depth / 400 mm Length 1.945 kg Ordering Minimum Order Quantity 1 piece Package Level 1 Units box 1 piece Package Level 1 Gross 2 220 kg Weight Certificates and Declarations Declaration of Conformity 9AKK108468A7088 -CE Installation Instructions and Manuals 9AKK107992A6837 Popular Downloads Data Sheet, Technical 11120406/448ET		0000 K
Degree of Protection IP68 Protection Class Isolated (Class II) Dimensions	Environmental	
Protection Class Isolated (Class II) Dimensions Product Net Width 114 mm Product Net Height 114 mm Product Net Depth / 400 mm Length 1.945 kg Ordering Minimum Order Quantity 1 piece Package Level 1 Units 50x 1 piece Package Level 1 Gross 2.220 kg Weight 2.220 kg Weight 9AKK108468A7088 Certificates and Declarations Declaration of Conformity 9AKK108468A7088 Installation Instructions and Manuals 9AKK107992A6837 Popular Downloads Data Sheet, Technical 11120406/448T	Ambient Temperature	0 40 °C
Dimensions Product Net Width 114 mm Product Net Height 114 mm Product Net Depth / 400 mm Length 1970 1985 kg Ordering Minimum Order Quantity 1 piece Package Level 1 Units 50x 1 piece Package Level 1 Gross 2.220 kg Weight 2.220 kg Certificates and Declarations Declaration of Conformity 9AKK108468A7088 -CE Installation Instructions and Manuals 9AKK107992A6837 Popular Downloads Data Sheet, Technical 11120406/448T	Degree of Protection	IP68
Product Net Width 114 mm Product Net Height 114 mm Product Net Depth / 400 mm Length 1.945 kg Ordering Minimum Order Quantity 1 piece Package Level 1 Units 50x 1 piece Package Level 1 Gross 2.220 kg Weight Certificates and Declarations Declaration of Conformity 9AKK108468A7088 -CE Installation Instructions and Manuals 9AKK107992A6837	Protection Class	Isolated (Class II)
Product Net Height 114 mm Product Net Depth / 400 mm Product Net Weight 1.945 kg Ordering Minimum Order Quantity 1 piece Package Level 1 Units 5 box 1 piece Package Level 1 Gross 2.220 kg Weight 2.220 kg Certificates and Declarations Declaration of Conformity 9AKK108468A7088 - CE Installation Instructions and Manuals 9AKK107992A6837	Dimensions	
Product Net Depth / Length Product Net Weight 1.945 kg Ordering Minimum Order Quantity 1 piece Package Level 1 Units 5 box 1 piece Package Level 1 Gross Weight Certificates and Declarations Declaration of Conformity 9AKK108468A7088 -CE Installation Instructions and Manuals Popular Downloads Data Sheet, Technical 11120406/448T	Product Net Width	114 mm
Product Net Depth / Length Product Net Weight 1.945 kg Ordering Minimum Order Quantity 1 piece Package Level 1 Units box 1 piece Package Level 1 Gross 2.220 kg Weight Certificates and Declarations Declaration of Conformity 9AKK108468A7088 -CE Installation Instructions and Manuals 9AKK107992A6837 Popular Downloads Data Sheet, Technical 11120406/448T	-	114 mm
Product Net Weight 1.945 kg Ordering Minimum Order Quantity 1 piece Package Level 1 Units box 1 piece Package Level 1 Gross 2.220 kg Weight 2.220 kg Certificates and Declarations Declaration of Conformity 9AKK108468A7088 - CE Installation Instructions and Manuals 9AKK107992A6837	Product Net Depth /	400 mm
Minimum Order Quantity Package Level 1 Units Dox 1 piece Package Level 1 Gross Package Level 1 Gross Veight Certificates and Declarations Declaration of Conformity - CE Installation Instructions and Manuals Popular Downloads Data Sheet, Technical 11120406/44BT		1.945 kg
Minimum Order Quantity Package Level 1 Units Dox 1 piece Package Level 1 Gross Package Level 1 Gross Veight Certificates and Declarations Declaration of Conformity - CE Installation Instructions and Manuals Popular Downloads Data Sheet, Technical 11120406/44BT	Ordering	
Package Level 1 Units box 1 piece Package Level 1 Gross Weight Certificates and Declarations Declaration of Conformity 9AKK108468A7088 - CE Installation Instructions and Manuals 9AKK107992A6837 Popular Downloads Data Sheet, Technical 11120406/44BT	·	1 piece
Package Level 1 Gross Weight Certificates and Declarations Declaration of Conformity 9AKK108468A7088 Installation Instructions and Manuals 9AKK107992A6837 Popular Downloads Data Sheet, Technical 11120406/44BT	•	•
Declaration of Conformity - CE Installation Instructions and Manuals Popular Downloads Data Sheet, Technical 9AKK108468A7088 9AKK107992A6837	Package Level 1 Gross	2.220 kg
Installation Instructions and Manuals Popular Downloads Data Sheet, Technical 11120406/44BT	Certificates and Declarations	
Popular Downloads Data Sheet, Technical 9AKK107992A6837		9AKK108468A7088
Popular Downloads Data Sheet, Technical 9AKK107992A6837		
Popular Downloads Data Sheet, Technical 11120406/44BT	Installation	
Data Sheet, Technical 11120406/44BT	Instructions and Manuals	9AKK107992A6837
Data Sheet, Technical 11120406/44BT	Popular Downloads	
		11120406/44BT

11120406/44BT 3

Classifications		
ETIM 8	EC001957 - Emergency luminaire	
ETIM 9	EC001957 - Emergency luminaire	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	
WEEE B2C / B2B	Business To Business	
CN8	9405490000	

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Installation\ Products\ \rightarrow\ Cable\ Protection,\ Explosion\ Proof\ and\ Lighting\ \rightarrow\ Emergency\ Lighting\ Products\ Products\ Profession\ Proof\ Proof$

