



 PRODUCT-DETAILS

DP30C3P-1/B

DP30C3P-1/B Contactor



General Information

Extended Product Type	DP30C3P-1/B
Product ID	1SBX103300B1200
EAN	0662019799957
Catalog Description	DP30C3P-1/B Contactor
Long Description	DP30C3P-1/B DP contactor provide outstanding performance in various HVAC application and meet all relevant standards, including UL, CSA and IEC. Industry standard mounting plate provides easily accessible mounting holes.

Ordering

Minimum Order Quantity	25 piece
Customs Tariff Number	85365080

Dimensions

Product Net Width	60.3 mm
Product Net Depth / Length	73.8 mm

Product Net Height	92 mm
Product Net Weight	0.45 kg

Technical

Number of Main Contacts NO	3
Standards	IEC 60947-4-1 UL 508
Rated Frequency (f)	Control Circuit 50 Hz Control Circuit 60 Hz
Rated Control Supply Voltage (U _s)	120 V AC

Environmental

Ambient Air Temperature	Operation -40 ... +65 °C
RoHS Status	No declaration needed

Technical UL/CSA

Horsepower Rating UL/CSA	(110 ... 120 V AC) Single Phase 2 Hp (208 V AC) Three Phase 10 Hp (220 ... 240 V AC) Single Phase 5 Hp (220 ... 240 V AC) Three Phase 10 Hp (440 ... 480 V AC) Three Phase 15 Hp (550 ... 600 V AC) Three Phase 20 Hp
Full Load Amps AC Resistance (Heating)	(600 V AC) 40 A
Full Load Amps Motor Use	30 A
Locked Rotor Amps	(480 V AC) 150 A (600 V AC) 120 A

Certificates and Declarations

cUL Certificate	cUL_E224401
Declaration of Conformity - CE	EN60947-4-1:2001
UL Certificate	UL_E224401

Container Information

Package Level 1 Units	25 piece
Package Level 1 Width	508 mm
Package Level 1 Depth / Length	101.6 mm
Package Level 1 Height	355.6 mm

Classifications

Object Classification Code	Q
ETIM 7	EC000066 - Power contactor, AC switching

Categories

Low Voltage Products and Systems → Control Products → Contactors → Definite Purpose Contactors

