




---

 PRODUCT-DETAILS

# DP30C3P-2/B

## DP30C3P-2/B Contactor




---

**General Information**

Extended Product Type	DP30C3P-2/B
Product ID	1SBX103300B1300
EAN	0804325314459
Catalog Description	DP30C3P-2/B Contactor
Long Description	DP30C3P-2/B DP contactor provide outstanding performance in various HVAC application and meet all relevant standards, including UL, CSA and IEC. Industry standard mounting plate provides easily accessible mounting holes.

---

**Ordering**

Minimum Order Quantity	25 piece
Customs Tariff Number	85365080

---

**Dimensions**

Product Net Width	60.3 mm
Product Net Depth / Length	73.8 mm

Product Net Height	92 mm
Product Net Weight	0.45 kg

## Technical

Number of Main Contacts NO	3
Standards	IEC 60947-4-1 UL 508
Rated Frequency (f)	Control Circuit 50 Hz Control Circuit 60 Hz
Rated Control Supply Voltage (U <sub>s</sub> )	208 / 240 V AC

## Environmental

Ambient Air Temperature	Operation -40 ... +65 °C
RoHS Status	No declaration needed

## Technical UL/CSA

Horsepower Rating UL/CSA	(110 ... 120 V AC) Single Phase 2 Hp (208 V AC) Three Phase 10 Hp (220 ... 240 V AC) Single Phase 5 Hp (220 ... 240 V AC) Three Phase 10 Hp (440 ... 480 V AC) Three Phase 15 Hp (550 ... 600 V AC) Three Phase 20 Hp
Full Load Amps AC Resistance (Heating)	(600 V AC) 40 A
Full Load Amps Motor Use	30 A
Locked Rotor Amps	(480 V AC) 150 A (600 V AC) 120 A

## Certificates and Declarations

cUL Certificate	cUL_E224401
Declaration of Conformity - CE	EN60947-4-1:2001
UL Certificate	UL_E224401

## Container Information

Package Level 1 Units	25 piece
Package Level 1 Width	508 mm
Package Level 1 Depth / Length	101.6 mm
Package Level 1 Height	355.6 mm

## Classifications

Object Classification Code	Q
ETIM 7	EC000066 - Power contactor, AC switching

---

## Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Definite Purpose Contactors

