



PRODUCT-DETAILS**OT200E32****OT200E32 SWITCH-DISCONNECTOR**

General Information

Extended Product Type	OT200E32
Product ID	1SCA103724R1001
EAN	6417019381008
Catalog Description	OT200E32 SWITCH-DISCONNECTOR
Long Description	5-pole, front operated, base mounted switch-diconductor, handle and shaft are not included, terminal bolt kit included

Circular Value

End of Life Instructions	1SCC301117M0201
--------------------------	-----------------

Eco Transparency

Environmental Product Declaration - EPD	1SCC301282D0201
---	-----------------

Environmental

Environmental Information	1SCC301265D0201
---------------------------	-----------------

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	1SCC011025D0201

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301031M0220
Mechanical Drawings	1SCC307637F0001 1SCC307636F0001 OT200-250E32.stp OT200E32.igs
Environmental Product Declaration - EPD	1SCC301282D0201
End of Life Instructions	1SCC301117M0201

Dimensions

Product Net Width	220.5 mm
Product Net Height	150 mm
Product Net Depth / Length	82.5 mm
Product Net Weight	2.1 kg

Technical

Rated Operational Current AC-21A (I _e)	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A (1000 V) 200 A
Rated Operational Current AC-21B (I _e)	(690 V) 200 A
Rated Operational Current DC-21B (I _e)	(800 V) 200 A
Conventional Free-air Thermal Current (I _{th})	Θ = 40 °C 200 A

Conventional Thermal Current (I_{the})	Fully Enclosed 200 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity (I_{cm})	(690 V) 30 kA
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 8 kA
Power Loss	at Rated Operating Conditions per Pole 4.0 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Switches Operating Mechanism	Mechanism Between the Poles
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3
Special Functions	No
Mounting Type	Base mounting
Number of Poles	5
Degree of Protection	Front IP00
Terminal Type	Lug terminals
Tightening Torque	acc. IEC 60947-1 15 ... 22 N·m
Mechanical Durability	20000
Lock Type	No

Technical UL/CSA

Tightening Torque	acc. IEC 60947-1 15 ... 22 N·m
-------------------	--------------------------------

Certificates and Declarations

A2L Certificate - IEC	1SCC301337D0201
Declaration of Conformity - CE	1SCC301162D2702
DNV GL Certificate	1SCC301174D0204

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	190 mm 7.5 in
Package Level 1 Depth / Length	290 mm 11.4 in
Package Level 1 Height	110 mm 4.3 in
Package Level 1 Gross Weight	2.3 kg 5.1 lb

Package Level 1 EAN

6417019381008

Classifications

Object Classification Code	Q
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

