




---

 PRODUCT-DETAILS

# OKA100P4YF41

## OKA100P4YF41 F400 EMC Enclosed Switch

"No longer for sale" replaced by




---

**General Information**

Extended Product Type	OKA100P4YF41
Product ID	1SCA157811R1001
EAN	6417019871356
Catalog Description	OKA100P4YF41 F400 EMC Enclosed Switch
Long Description	F400 EMC Enclosed Switch Disconnecter, 4-p. 415V AC23 61A, 30kW. Mounted auxiliary contact: 1NO0NC. Aluminium enclosure. IP65. RedYellow Pistol handle. No interlocked cover. No defeatable interlocking. The ABB fire rated switches withstand fire acc. to standard EN12101-3. ABB can provide products for class F200 (120min), F300 (120min) and F400 (120min). Typical applications are high rise buildings, car parks, tunnels or any other place where there are exhaust fans that should stay on during fire. The enclosure is made of rigid aluminium alloy, or painted steel sheet. The F200 and F400 products are also available with auxiliary contacts. The products are EMC approved, when used with EMC cable glands. The handle is padlockable. Versions for padlockable in Off, or On and Off state, are available.

---

**Material Compliance**

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC340076D0201
RoHS Information	1SCC340075D0201

RoHS Status

Following EU Directive 2011/65/EU

---

**Ordering**


---

Minimum Order Quantity	1 piece
Customs Tariff Number	85363030
Replacement Product ID (NEW)	OKL80P4Y1F400
Country of Origin	Spain (ES)

---



---

**Popular Downloads**


---

Data Sheet, Technical Information	1SCC340004B0201
Instructions and Manuals	1SCC340174M0201
Mechanical Drawings	GV6252511PM40.stp

---



---

**Dimensions**


---

Product Net Width	250 mm
Product Net Height	250 mm
Product Net Depth / Length	111 mm
Product Net Weight	3.403 kg

---



---

**Technical**


---

Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 94 A (500 V) 94 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 61 A (500 V) 61 A
Rated Operational Power AC-23A ( $P_e$ )	(380 ... 415 V) 30 kW (500 V) 37 kW
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 100 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	4 kV
Rated Insulation Voltage ( $U_i$ )	acc. to IEC/EN 60664-1 690 V
Rated Operational Voltage	Main Circuit 500 V
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 1.2 kA
Rated Conditional Short-Circuit Current ( $I_{nc}$ )	8 kA
Pollution Degree	3
Handle Color	Red / Yellow
Handle Type	Pistol handle
Position of Line Terminals	Top In - Bottom Out
Standards	IEC 60947-1, -3 EN12101-3:2015
Special Functions	EMC
Number of Poles	4
Neutral Type	Switchable neutral
Connecting Capacity Main Circuit	Screw Clamp 6 ... 50 mm <sup>2</sup> Screw Clamp / PE Terminal 2pc.6 ... 50 mm <sup>2</sup>
Cable Cross-Section	6 ... 50 mm <sup>2</sup>
Cable Entry Position	Up/Down

Cable Outlets Per Side	1xM40 / 1xM40
Degree of Protection	acc. to IEC 60529 IP65
Impact Resistance Rating	Housing IK09
Enclosure Type	GV6
Enclosure Material	Aluminium
Maximum Mounted Auxiliary Contacts	1 NO, 0 NC
Mounted Auxiliary Contacts	1 NO, 0 NC
Number of Auxiliary Contacts NC	0
Number of Auxiliary Contacts NO	1
Terminal Type	Screw Terminals
Tightening Torque	Main Circuit 3.5 N·m
Mechanical Durability	20000

### Technical UL/CSA

Tightening Torque	Main Circuit 3.5 N·m
-------------------	----------------------

### Certificates and Declarations

CB Certificate	CB OK_25-125_YF4 TC F400 OK_63-125_YF4
Declaration of Conformity - CE	1SCC340070D2701

### Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	178 mm
Package Level 1 Depth / Length	255 mm
Package Level 1 Height	255 mm
Package Level 1 Gross Weight	3.571 kg
Package Level 1 EAN	6417019871356

### Classifications

Object Classification Code	Q
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

## Categories

---

Low Voltage Products and Systems → Enclosed Switches → Enclosed Switch-Disconnectors → Fire Rated Enclosed Switch-Disconnectors

