




---

 PRODUCT-DETAILS

# E3H2500PR122/DCIn=2500A4pWMP

## E3H 2500 PR122/DC In=2500A 4p W MP




---

**General Information**

Extended Product Type	E3H2500PR122/DCIn=2500A4pWMP
Product ID	1SDA064635R1
EAN	8015644675288
Catalog Description	E3H 2500 PR122/DC In=2500A 4p W MP
Long Description	SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3H 2500A FOUR-POLE OVERCURRENT RELEASE PR122/DC R2500 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

---

**Environmental**

Environmental Information	9AKK10103A6076
---------------------------	----------------

---

**Material Compliance**

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template	Document availability on demand

(CMRT)

Toxic Substances Control  
Act - TSCA

9AKK108467A8326

**Ordering**

EAN	8015644675288
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

**Dimensions**

Product Net Width	558 mm
Product Net Height	461 mm
Product Net Depth / Length	396.5 mm
Product Net Weight	81 kg

**Container Information**

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	600 mm
Package Level 1 Depth / Length	785 mm
Package Level 1 EAN	8015644609139

**Additional Information**

Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Version	W

**Technical**

Current Type	DC
Electrical Durability	Ue = 1000 V 7000 cycle
Mechanical Durability	20000 cycle 60 cycles per hour
Number of Poles	4
Power Loss	500 W
Rated Current ( $I_n$ )	2500 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Current ( $I_e$ )	2500 A
Rated Operational Voltage	1000 V DC
Rated Service Short- Circuit Breaking Capacity ( $I_{cs}$ )	(750 V DC) 50 kA (1000 V DC) 40 kA
Rated Ultimate Short- Circuit Breaking Capacity ( $I_{cu}$ )	(750 V DC) 50 kA (1000 V DC) 40 kA
Rated Uninterrupted Current ( $I_u$ )	2500 A

Rated Voltage (U <sub>r</sub> )	1000 V
Release	PR122/DC
Release Type	EL
Short-Circuit Performance Level	H
Standards	IEC
Sub-type	E3
Terminal Connection Type	Withdrawable Circuit-Breakers

## Certificates and Declarations

Data Sheet, Technical Information	1SDC200012D0202
Declaration of Conformity - CE	1SDL000165R0015
Instructions and Manuals	1SDH000635R0002

## Classifications

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

## Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax

