



 PRODUCT-DETAILS

E1.2N-A 1200 Ekip Dip LSI 3p WMP

E1.2N-A 1200 Ekip Dip LSI 3p WMP



General Information

Extended Product Type	E1.2N-A 1200 Ekip Dip LSI 3p WMP
Product ID	1SDA077099R1
EAN	8015644835224
Catalog Description	E1.2N-A 1200 Ekip Dip LSI 3p WMP
Long Description	MOVING PART FOR C.BREAKER SACE EMAX2 E1.2N-A 1200 UL THREE-POLE WITH SOLID -STATE RELEASE IN AC EKIP/DIP-LSI R 1200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions

ABB EcoSolutions	Yes
------------------	-----

Circular Value

Circular Design	Design for Closing Resource Loops - Standard EN45555 - 76.4 %
Principles Recyclability Rate	
End of Life Instructions	9AKK108468A2360

Group Waste to Landfill
Target

UL 2799 Zero Waste To Landfill Validation available

Eco Transparency

Environmental Product Declaration - EPD 9AKK108468A1901

Environmental

Environmental Information 9AKK108467A6707

Material Compliance

REACH Declaration 9AKK108466A1425
 RoHS Information 9AKK108466A1424
 RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
 Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
 Toxic Substances Control Act - TSCA 9AKK108467A8326

Ordering

Order Code US and Canada Z1NDUHAB000A000000XX
 EAN 8015644835224
 Minimum Order Quantity 1 piece
 Customs Tariff Number 85362090

Dimensions

Product Net Width 278 mm
 Product Net Height 363.5 mm
 Product Net Depth / Length 281 mm
 Product Net Weight 14 kg

Container Information

Package Level 1 Units box 1 piece
 Package Level 1 Width 365 mm
 Package Level 1 Height 350 mm
 Package Level 1 Depth / Length 330 mm
 Package Level 1 Gross Weight 22 kg
 Package Level 1 EAN 8015644835224

Additional Information

© 2024 ABB. All rights reserved.

2024/10/06

Subject to change without notice

Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Version	W

Technical

Current Type	AC
Electrical Durability	Ue =< 508 V 7000 cycle Ue = 508 ... 635 V 6500 cycle 30 cycles per hour
Mechanical Durability	20000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 250 W
Rated Current (I _n)	1200 A
Rated Insulation Voltage (U _i)	AC 635 V
Rated Operational Voltage	600 V AC
Rated Voltage (U _r)	600 V
Release	Ekip Dip LSI
Release Type	EL
Short-Circuit Performance Level	N
Standards	UL
Sub-type	E1.2

Technical UL/CSA

Interrupting Rating acc. to UL1066	(254 V) 50 kA (508 V) 50 kA (635 V) 42 kA
------------------------------------	---

Certificates and Declarations

Data Sheet, Technical Information	1SXU200040C0201
Declaration of Conformity - CE	9AKK106713A5546
Instructions and Manuals	1SDH000999R0002

Classifications

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

