



 PRODUCT-DETAILS

E2.2V-A 2000 Ekip Dip LSIG 3p F HR

E2.2V-A 2000 Ekip Dip LSIG 3p F HR



General Information

Extended Product Type	E2.2V-A 2000 Ekip Dip LSIG 3p F HR
Product ID	1SDA077390R1
EAN	8015644838133
Catalog Description	E2.2V-A 2000 Ekip Dip LSIG 3p F HR
Long Description	C.BREAKER SACE EMAX2 E2.2V-A 2000 UL FIXED THREE-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/DIP-LSIG R 2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions

ABB EcoSolutions	Yes
------------------	-----

Circular Value

Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 79.1 %
End of Life Instructions	9AKK108468A2361

Group Waste to Landfill
Target

UL 2799 Zero Waste To Landfill Validation available

Eco Transparency

Environmental Product Declaration - EPD 9AKK108468A1906

Environmental

Environmental Information 9AKK108467A6707

Material Compliance

REACH Declaration 9AKK108466A1425
 RoHS Information 9AKK108466A1424
 RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
 Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
 Toxic Substances Control Act - TSCA 9AKK108467A8326
 SCIP 5db9272f-d385-4a4a-a0e6-73274e7613b2 Italy (IT)

Ordering

Order Code US and Canada Z2VFUKBC000A000000XX
 EAN 8015644838133
 Minimum Order Quantity 1 piece
 Customs Tariff Number 85362090

Dimensions

Product Net Width 276 mm
 Product Net Height 371 mm
 Product Net Depth / Length 270 mm
 Product Net Weight 45 kg

Container Information

Package Level 1 Units box 1 piece
 Package Level 1 Width 515 mm
 Package Level 1 Height 610 mm
 Package Level 1 Depth / Length 515 mm
 Package Level 1 Gross Weight 50 kg
 Package Level 1 EAN 8015644838133

Additional Information

Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Version	F

Technical

Current Type	AC
Electrical Durability	Ue = < 508 V 10000 cycle Ue = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	25000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 250 W
Rated Current (I _n)	2000 A
Rated Insulation Voltage (U _i)	AC 635 V
Rated Operational Voltage	600 V AC
Rated Voltage (U _r)	600 V
Release	Ekip Dip LSIG
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL
Sub-type	E2.2
Terminal Connection Type	Rear flat Horizontal

Technical UL/CSA

Interrupting Rating acc. to UL1066	(254 V) 100 kA (508 V) 100 kA (635 V) 85 kA
------------------------------------	---

Certificates and Declarations

Data Sheet, Technical Information	1SXU200040C0201
Declaration of Conformity - CE	9AKK106713A5902
Instructions and Manuals	1SDH001000R0002

Classifications

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
UNSPSC	39121615

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

eClass

V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

