



PRODUCT-DETAILS

DR M16 HI 1600 3p to E2.2/MS int

DR M16 HI 1600 3p to E2.2/MS int

General Information

Extended Product Type	DR M16 HI 1600 3p to E2.2/MS int
Product ID	1SDA124492R1
EAN	8056221250085
Catalog Description	DR M16 HI 1600 3p to E2.2/MS int
Long Description	Direct Replacement M16 HI 1600 3p to E2.2/MS - Service customization

Technical

Standards	IEC
Current Type	AC
Rated Voltage (U_r)	690 V
Rated Operational Voltage	690 V AC
Rated Current (I_n)	1600 A
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 50 kA
Number of Poles	3

Version	W
Configuration Type	Mounted only
Product Type	Direct Replacement Merlin Gerin/Schneider Masterpact M to Emax 2 IEC
Sub-type	E2.2

Material Compliance

RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
REACH Declaration	9AKK108466A1425
Conflict Minerals Reporting Template (CMRT)	Document availability on demand

Ordering

Package Level 1 Units	pallet (lift) 1 piece
EAN	8056221250085

Installation

Instructions and Manuals	1SDH001612R0001
Wiring Diagram	1SDM000106R0001

Popular Downloads

Data Sheet, Technical Information	1SDC001146L0204
-----------------------------------	-----------------

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85389099

Additional Information

Product Main Type	Low Voltage retrofit with Emax 2
-------------------	----------------------------------

Categories

Low Voltage Products and Systems → Service → Extensions, Upgrades and Retrofits → Retrofits