RB121-24VDC 1/3



PRODUCT-DETAILS

RB121-24VDC RB121-24VDC Interface relay R600 1c/o,A1-A2=24VDC,5-250VAC/60mA-6A



General Information	
Extended Product Type	RB121-24VDC
Product ID	1SNA645071R0000
EAN	4013614508134
Catalog Description	RB121-24VDC Interface relay R600 1c/o,A1-A2=24VDC,5-250VAC/60mA-6A
Long Description	The RB121-24VDC is a boxed interface relay with screw terminals, which can be seemlessly snap-on mounted onto a DIN Rail. The relay is soldered into device housing, ensuring a high resistance against vibration. This relay operates with a 24 V DC rated control supply voltage and has a 1 c/o (SPDT) output with contacts rated at 250 V / 6 A. This 6mm wide boxed interface relay may be used for electrical isolation, amplification and signal matching and enables the switching of high currents on a small footprint. It has an integrated LED, which provides the visual indication of the energization of the relay coil and UL 94-V0 certified device housing, improving safety by providing high levels flame retardation. Jumper bars are available as accessories.

Ordering	
EAN	4013614508134
Minimum Order Quantity	10 piece
Customs Tariff Number	85364900

RB121-24VDC 2/3

Popular Downloads	
Data Sheet, Technical Information	2CDC110004C0210_05
Instructions and Manuals	1SVC645000M9000
CAD Dimensional <u>Drawing</u>	2CDC001079B0201

Dimensions	
Product Net Width	6 mm
Product Net Height	67.5 mm
Product Net Depth / Length	70 mm
Product Net Weight	0.02 kg

Technical	
Function	Boxed interface relay R600
Sub-Function	Relay with built in LED
Rated Control Supply Voltage (U_s)	24 V DC
Output	1 c/o (SPDT) contact
Output Signal	5 250VAC / 60mA 6A
Terminal Type	Screw Terminals
Degree of Protection	IP20
Standards	CAN/CSA C22.2 No.14 IEC/EN 63000 IEC/EN 60947-5-1 UL 508

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006525

Certificates and Declarations	
CB Certificate	CB_DK-53188-UL
CCC Certificate	CCC_2017010303941444
CQC Certificate	CQC_2017010303941444
CSA Certificate	CSA_254821
cUR Certificate	cUR_E352056
Declaration of Conformity - CCC	CCC_2020980303000254
Declaration of Conformity - CE	1SVD982016-0001
Declaration of Conformity - UKCA	1SVD982016-1000
LR Certificate	LR 16 20068
UR Certificate	UR E352056

RB121-24VDC 3/3

Container Information	
Package Level 1 Units	box 10 piece
Package Level 1 Width	73 mm
Package Level 1 Depth / Length	80 mm
Package Level 1 Height	71 mm
Package Level 1 Gross Weight	0.23 kg
Package Level 1 EAN	3472596450717

Classifications	
Object Classification Code	К
ETIM 7	EC001437 - Switching relay
ETIM 8	EC001437 - Switching relay
ETIM 9	EC001437 - Switching relay
eClass	V11.0 : 27371601
UNSPSC	39122331

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Control\ Products\ \rightarrow\ Electronic\ Relays\ and\ Controls\ \rightarrow\ Interface\ Relays\ and\ Optocouplers$

