

PRODUCT-DETAILS

MLA2 Main Lug Kit



General Information	
Global Commercial Alias	MLA2
Extended Product Type	MLA2
Product ID	1TQR162000Z1000
EAN	not available
Catalog Description	Main Lug Kit
Long Description	ReliaGear lighting panelboards are factory assembled on rigid steel frames and equipped with circuit breakers from 15 A to 800 A. The maximum fully-rated short circuit rating is equal to 65 kAIC to 240 V AC and 480/277 V AC.

ABB EcoSolutions	
ABB EcoSolutions	Yes
Circular Design Principles Recyclability Rate	92.6 %
Offered with Extended Lifetime	Product Modularity
End of Life Instructions	1SQC173021M0202
Environmental Product	1SQC173004D0201

MLA2 2/3

Declaration - EPD

Technical	
Rated Voltage (Ur)	480 V AC
Rated Current (I _n)	225 V AC
Model Number	MLA2
Number of Poles	3
Cable Cross-Section	600 kcmil
Connecting Capacity Main Circuit	600 kcmil
Terminal Type	Lug terminals

Dimensions	
Product Net Width	5.812 in
Product Net Height	2.000 in
Product Net Depth / Length	11.625 in
Product Net Weight	2.460 lb

Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	variable lb

Certificates and Declarations	
Declaration of	No declaration needed
Conformity - CE	

Installation	
Installation Manual	1TQC213000Z0015
Instructions and	No document needed
Manuals	

Classifications	
ETIM 8	EC002021 - Terminal block connector
ETIM 9	EC002021 - Terminal block connector
WEEE Category	Product Not in WEEE Scope
UNSPSC	39121724
eClass	V11.1 : 27141151
IDEA Granular Category Code (IGCC)	4666 >> Wire terminal connector kit

MLA2 3/3

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow NEMA\ Residential\ and\ Commercial\ Portfolio \rightarrow Lighting\ Panels\ \&\ Breakers \rightarrow PROSTOCK\ Lighting\ Panels$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow NEMA\ Residential\ and\ Commercial\ Portfolio \rightarrow Lighting\ Panels\ \&\ Breakers \rightarrow ReliaGear\ Lighting\ Panels$









