
MLR42 1/3



PRODUCT-DETAILS

## MLR42 Main Lug Kit



General Information		
Global Commercial Alias	MLR42	
Extended Product Type	MLR42	
Product ID	1TQR162004Z1001	
EAN	not available	
Catalog Description	Main Lug Kit	
Long Description	ReliaGear lighting panelboards are factory assembled on rigid steel frames and equipped with circuit breakers from 15 A to 800 A. The maximum fully-rated short circuit rating is equal to 65 kAIC to 240 V AC and 480/277 V AC.	

Technical	
Rated Voltage (U <sub>r</sub> )	480 V AC
Rated Current (In)	400 V AC
Model Number	MLR42
Number of Poles	3
Cable Cross-Section	600 kcmil
Connecting Capacity Main Circuit	600 kcmil

MLR42 2/3

Terminal Type Lug terminals **Dimensions Product Net Width** 0.001 in Product Net Height 0.001 in Product Net Depth / 0.001 in Length **Product Net Weight** 0.001 lb **Ordering** Package Level 1 Units box 1 piece **Certificates and Declarations** Declaration of No declaration needed Conformity - CE Installation Instructions and No document needed Manuals **Popular Downloads** 9AKK107680A9334 Data Sheet, Technical Information Classifications ETIM 8 EC002021 - Terminal block connector ETIM 9 EC002021 - Terminal block connector Product Not in WEEE Scope WEEE Category UNSPSC 39121446 eClass V11.1 : 27141151 4666 >> Wire terminal connector kit **IDEA Granular Category** 

Code (IGCC)

MLR42 3/3

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow NEMA\ Residential\ and\ Commercial\ Portfolio \rightarrow Lighting\ Panels\ \&\ Breakers \rightarrow PROSTOCK\ Lighting\ Panels$ 











