


PRODUCT-DETAILS





General Information	
Global Commercial Alias	AB82BP
Extended Product Type	AB82BP
Product ID	1TQR282100N1000
EAN	not available
Catalog Description	Enclosure
Long Description	ReliaGear lighting panelboards are factory assembled on rigid steel frames and equipped with circuit breakers from 15 A to 800 A. The maximum fully-rated short circuit rating is equal to 65 kAIC to 240 V AC and 480/277 V AC.

ABB EcoSolutions	
ABB EcoSolutions	Yes
Circular Design Principles Recyclability Rate	92.6 %
Offered with Extended Lifetime	Product Modularity
End of Life Instructions	1SQC173021M0202
Environmental Product	1SQC173004D0201

© 2024 ABB. All rights reserved.

2024/10/15

Subject to change without notice

Dimensions	
Product Net Width	20.000 in
Product Net Height	82.500 ir
Product Net Depth / Length	5.750 ir
Product Net Weight	80.000 lk
Ordering	
Package Level 1 Units	box variable piece
Package Level 1 Gross Weight	variable Ib
Certificates and Declarations	
Declaration of Conformity - CE	No declaration needec
Installation	
Instructions and Manuals	No document needec
Popular Downloads	
Data Sheet, Technical Information	9AKK107680A9334
Building Information Modeling – BIM	1SQC173009D0201
Classifications	
WEEE Category	Product Not in WEEE Scope
UNSPSC	39121321
IDEA Granular Category Code (IGCC)	4465 >> Enclosure General Accessories

## Categories

Low Voltage Products and Systems  $\rightarrow$  NEMA Residential and Commercial Portfolio  $\rightarrow$  Lighting Panels & Breakers  $\rightarrow$  ReliaGear Lighting Panels

