AF31SPYUM 1/3



PRODUCT-DETAILS

AF31SPYUM

Front



General Information	
Global Commercial Alias	AF31SPYUM
Extended Product Type	AF31SPYUM
Product ID	1TQR331102D2300
EAN	783164484366
Catalog Description	Front
Long Description	ReliaGear lighting panelboards are factory assembled on rigid steel frames and equipped with circuit breakers from 15 A to 800 A. The maximum fully-rated short circuit rating is equal to 65 kAIC to 240 V AC and 480/277 V AC.

ABB EcoSolutions	
ABB EcoSolutions	Yes
Circular Design Principles Recyclability Rate	92.6 %
Offered with Extended Lifetime	Product Modularity
End of Life Instructions	1SQC173021M0202
Environmental Product	1SQC173004D0201

AF31SPYUM 2/3

Declaration - EPD

Dimensions	
Product Net Width	20.000 in
Product Net Height	31.500 in
Product Net Depth / Length	0.100 in
Product Net Weight	20.000 lb

Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	26.840 lb

Certificates and Declarations	
Declaration of Conformity - CE	No declaration needed
	No declaration r

Installation	
Instructions and	No document needed
Manuals	

Popular Downloads	
Data Sheet, Technical Information	9AKK107680A9334

Classifications	
WEEE Category	Product Not in WEEE Scope
UNSPSC	39121321
IDEA Granular Category Code (IGCC)	4465 >> Enclosure General Accessories

Categories

AF31SPYUM 3/3

 $Low\ Voltage\ Products\ and\ Systems \rightarrow NEMA\ Residential\ and\ Commercial\ Portfolio \rightarrow Lighting\ Panels\ \&\ Breakers \rightarrow ReliaGear\ Lighting\ Panels$

