




---

 PRODUCT-DETAILS

# AF55SPLW

## Front




---

### General Information

Global Commercial Alias	AF55SPLW
Extended Product Type	AF55SPLW
Product ID	1TQR355131D0000
EAN	not available
Catalog Description	Front
Long Description	ReliaGear lighting panelboards are factory assembled on rigid steel frames and equipped with circuit breakers from 15 A to 800 A. The maximum fully-rated short circuit rating is equal to 65 kAIC to 240 V AC and 480/277 V AC.

---

### ABB EcoSolutions

ABB EcoSolutions	Yes
Circular Design Principles Recyclability Rate	92.6 %
Offered with Extended Lifetime	Product Modularity
End of Life Instructions	1SQC173021M0202
Environmental Product Declaration - EPD	1SQC173004D0201

---

### Dimensions

---

Product Net Width	30.000 in
Product Net Height	55.500 in
Product Net Depth / Length	0.100 in
Product Net Weight	52.000 lb

---

---

### Ordering

---

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	67.310 lb

---

---

### Certificates and Declarations

---

Declaration of Conformity - CE	No declaration needed
--------------------------------	-----------------------

---

---

### Installation

---

Instructions and Manuals	No document needed
--------------------------	--------------------

---

---

### Popular Downloads

---

Data Sheet, Technical Information	9AKK107680A9334
-----------------------------------	-----------------

---

---

### Classifications

---

WEEE Category	Product Not in WEEE Scope
UNSPSC	39121321
IDEA Granular Category Code (IGCC)	4465 >> Enclosure General Accessories

---

---

### Categories

---

Low Voltage Products and Systems → NEMA Residential and Commercial Portfolio → Lighting Panels & Breakers → ReliaGear Lighting Panels

