




---

 PRODUCT-DETAILS

# AF76SDLN

## Front




---

### General Information

Global Commercial Alias	AF76SDLN
Extended Product Type	AF76SDLN
Product ID	1TQR376101F1000
EAN	not available
Catalog Description	Front
Long Description	ReliaGear lighting panelboards are factory assembled on rigid steel frames and equipped with circuit breakers from 15 A to 800 A. The maximum fully-rated short circuit rating is equal to 65 kAIC to 240 V AC and 480/277 V AC.

---

### ABB EcoSolutions

ABB EcoSolutions	Yes
Circular Design Principles Recyclability Rate	92.6 %
Offered with Extended Lifetime	Product Modularity
End of Life Instructions	1SQC173021M0202
Environmental Product	1SQC173004D0201

## Declaration - EPD

**Dimensions**

Product Net Width	20.000 in
Product Net Height	76.500 in
Product Net Depth / Length	0.100 in
Product Net Weight	48.000 lb

**Ordering**

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	62.740 lb

**Certificates and Declarations**

Declaration of Conformity - CE	No declaration needed
--------------------------------	-----------------------

**Installation**

Instructions and Manuals	No document needed
--------------------------	--------------------

**Popular Downloads**

Data Sheet, Technical Information	9AKK107680A9334
-----------------------------------	-----------------

**Classifications**

WEEE Category	Product Not in WEEE Scope
UNSPSC	39121321
IDEA Granular Category Code (IGCC)	4465 >> Enclosure General Accessories

**Categories**

Low Voltage Products and Systems → NEMA Residential and Commercial Portfolio → Lighting Panels & Breakers → ReliaGear Lighting Panels

