AQL3966NBXAXB6M7RO



PRODUCT-DETAILS

# AQL3966NBXAXB6M7RO

## **LP OEM Interior**



General Information	
Global Commercial Alias	AQL3966NBXAXB6M7RO
Extended Product Type	AQL3966NBXAXB6M7RO
Product ID	1TQR419602A0000
Catalog Description	LP OEM Interior
Long Description	ReliaGear lighting panelboards are factory assembled on rigid steel frames and equipped with circuit breakers from 15 A to 800 A. The maximum fully-rated short circuit rating is equal to 65 kAIC to 240 V AC and 480/277 V AC.

#### **Certificates and Declarations**

Declaration of No declaration needed Conformity - CE

#### Classifications

WEEE Category Product Not in WEEE Scope
UNSPSC 39121103
IDEA Granular Category 4349 >> Three Phase Main Lug Bolt-On Lighting Panelboard Interiors

© 2024 ABB. All rights reserved.

2024/10/15

Subject to change without notice

AQL3966NBXAXB6M7RO 2/2

Code (IGCC)

### **Categories**

 $Low\ Voltage\ Products\ and\ Systems \rightarrow NEMA\ Residential\ and\ Commercial\ Portfolio \rightarrow Lighting\ Panels\ \&\ Breakers \rightarrow ReliaGear\ Lighting\ Panels$ 

