



 PRODUCT-DETAILS

1VCF337686R0124

VD4/GT/P 40.06.16 P280 190BIL



General Information

Product ID	1VCF337686R0124
Catalog Description	VD4/GT/P 40.06.16 P280 190BIL

Certificates and Declarations

Data Sheet, Technical Information	1VCP000001_A
Instructions and Manuals	1VCD601314
Dimension Diagram	GCEM700198

Dimensions

Product Net Weight	280 kg
--------------------	--------

Additional Information

Standards	IEC 62271-100, .
Rated Voltage (U_r)	40,5 kV

Rated Impulse Withstand Voltage (U_{imp})	190 kV
Power Frequency Withstand Voltage	95 kV
Rated Frequency (f)	50/60 Hz
Rated Current (I_n)	630 A
Rated Short-time Withstand Current Low Voltage (I_{cw})	16 kA
Rated Short-Circuit Capacity	16 kA
Rated Short-Circuit Making Capacity (I_{cm})	40 kA
Operating Sequence	O-0,3S-CO-15S-CO
Ambient Temperature	-5 ... 40 °C
Product Main Type	VD4
Product Name	VD4/GT/P 40.06.16 P280 190BIL
Distance Between Phases	280 mm

Categories

Medium Voltage Products and Systems → Circuit Breakers → Indoor Vacuum Circuit Breakers

