



PRODUCT-DETAILS

1VCF370115R0665

VD4-AF 36.25.40 P360



General Information

Product ID	1VCF370115R0665
Catalog Description	VD4-AF 36.25.40 P360

Certificates and Declarations

Data Sheet, Technical Information	1VCP000771
Instructions and Manuals	1VCP000778
Dimension Diagram	2RDA034677

Dimensions

Product Net Weight	235 kg
--------------------	--------

Additional Information

Standards	IEC 62271-100
Rated Voltage (U_r)	36 kV
Rated Impulse Withstand Voltage (U_{imp})	190 kV
Power Frequency Withstand Voltage	95 kV
Rated Frequency (f)	50/60 Hz
Rated Current (I_n)	2500 A
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 3 s 40 kA
Rated Short-Circuit Capacity	40 kA DC Component 30 %
Rated Short-Circuit Making Capacity (I_{cm})	104 kA
Operating Sequence	O-0,3S-CO-15S-CO
Suitable for Product Class	M2
Ambient Temperature	-5 ... 40 °C
Product Main Type	VD4-AF
Product Name	VD4-AF 36.25.40 P360
Distance Between Phases	360 mm

Categories

Medium Voltage Products and Systems → Circuit Breakers → Indoor Vacuum Circuit Breakers

