



PRODUCT-DETAILS

FS463MK-C32/0.03

Residual Current Circuit Breaker with Overcurrent Protection



General Information

Extended Product Type	FS463MK-C32/0.03
Product ID	2CCL463310E0324
EAN	7612271470593
Catalog Description	Residual Current Circuit Breaker with Overcurrent Protection
Long Description	Residual current operated circuit breaker with overcurrent protection 3LN Type F for DIN

Technical

Standards	IEC/EN 61009
Tripping Characteristic	C
Type of Residual Current	Type F
Rated Operational Voltage	acc. to IEC 60898-1 415 V
Rated Insulation Voltage (U _i)	acc. to IEC/EN 60664-1 500 V
Rated Impulse Withstand Voltage (U _{imp})	4 kV

Input Voltage Type	AC
Rated Current (I_n)	32 A
Rated Residual Current	30 mA
Rated Short-Circuit Capacity	10 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	15 kA
Rated Conditional Short-Circuit Current (I_{nc})	10 kA
Rated Service Short-Circuit Breaking Capacity, in % of I_{cu} (I_{cs})	10 kA
Maximum Surge Current	3 kA
Rated Frequency (f)	50 ... 60 Hz
Energy Limiting Class	3
Number of Protected Poles	3
Number of Poles	4
Operating Characteristic	Instantaneous (APR High Immunity)
Overvoltage Category	III
Position of Neutral Terminals	Right
Earthing Switch Type	Short-Time Delayed
Options Provided	Smissline Classic
Accessories Available	Yes
Connecting Capacity	Stranded 0.75 ... 35 mm ² Flexible 0.75 ... 25 mm ²
Rated Cross-Section	1 - Solid-Core 0.75 ... 35 mm ² 4 - Multi-Wired 0.75 ... 10 mm ²

Material Compliance

RoHS Information	2CCC413008D0206_RoHS
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
RoHS Date	20170426
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Air Temperature	Operation -25 ... 60 °C
Degree of Protection	IP2X
Pollution Degree	2
Environmental Information	9AKK108467A9561

Technical UL/CSA

Short-Circuit Current Rating (SCCR)	0.03 A
-------------------------------------	--------

Dimensions

Width in Number of Modular Spacings	4
Product Net Width	72 mm
Product Net Height	76 mm
Product Net Depth / Length	87 mm
Product Net Weight	455 g
Built-In Depth (t ₂)	91 mm
Dimension Diagram	2CCC451027C0106 Ind B

Ordering

Package Level 1 Units	carton 1 piece
Package Level 1 Gross Weight	425 g
E-Number (Switzerland)	809182972
Replacement Product ID (NEW)	2CCG001849R0001

Certificates and Declarations

Declaration of Conformity - CE	2CCC005112D0201
--------------------------------	-----------------

Installation

Instructions and Manuals	9AKK107680A1666
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	2CCC451027C0106 Ind B
-----------------------------------	-----------------------

Classifications

ETIM 8	EC000905 - Earth leakage circuit breaker
ETIM 9	EC000905 - Earth leakage circuit breaker
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85362020
eClass	V11.0 : 27142207
Object Classification Code	FB

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → SMISLINE Classic → SMISLINE Classic

