



 PRODUCT-DETAILS

S203CT-C6

Miniature circuit breaker - 3P - C - 6 A



General Information

Extended Product Type	S203CT-C6
Product ID	2CDS233280R0064
EAN	4053546043839
Catalog Description	Miniature circuit breaker - 3P - C - 6 A
Long Description	The S203C series miniature circuit breaker is a 3P device in 2 modules for the protection of circuits against overload and short circuit.

ABB EcoSolutions

ABB EcoSolutions	Yes
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 85.36 %
Circular Design Principles Resource Reduction	Design for Reduced Resource Consumption - 52 %
Sustainable Material Content in Packaging	FSC 100% Cardboard - 100 %
Improved Resource	Product Efficiency - Product considered more energy-efficient compared

Efficiency for Customers	to similar product on market or older products from the same line
Offered with Extended Lifetime	Product Durability
End of Life Instructions	9AKK108468A3913
Environmental Product Declaration - EPD	9AKK108467A5789

Technical

Standards	IEC/EN 60898-1
Tripping Characteristic	C
Rated Operational Voltage	acc. to IEC 60898-1 415 V
Rated Insulation Voltage (U _i)	acc. to IEC/EN 60664-1 500 V
Rated Impulse Withstand Voltage (U _{imp})	4 kV
Input Voltage Type	AC
Rated Current (I _n)	6 A
Rated Short-Circuit Capacity	(230 V) 3 kA (400 V) 3 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(230 V) 3 kA (400 V) 3 kA
Rated Conditional Short-Circuit Current (I _{nc})	(230 V) 3 kA (400 V) 3 kA
Rated Frequency (f)	50/60 Hz
Power Loss	4.6 W
Power Supply Connection	Arbitrary
Energy Limiting Class	3
Electrical Endurance	10000 cycle
Mechanical Endurance	20000 cycle
Number of Protected Poles	3
Number of Poles	3
Overvoltage Category	III
Options Provided	G2C accessories
Accessories Available	Yes
Connecting Capacity	Flexible 1 ... 10 mm ² Rigid 1 ... 16 mm ²

Material Compliance

RoHS Information	9AKK107492A9802
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20191001
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Air Temperature	Operation -25 ... 55 °C
-------------------------	-------------------------

Degree of Protection	IP20
Pollution Degree	2

Dimensions

Width in Number of Modular Spacings	2
Product Net Width	36 mm
Product Net Height	86 mm
Product Net Depth / Length	70 mm
Product Net Weight	0.32 kg
Built-In Depth (t ₂)	70 mm

Ordering

Package Level 1 Units	carton 6 piece
Package Level 1 Gross Weight	1.97 kg

Certificates and Declarations

Declaration of Conformity - CE	9AKK107492A9802
Certification Agency	EN IEC

Installation

Instructions and Manuals	No document needed
--------------------------	--------------------

Popular Downloads

Data Sheet, Technical Information	9AKK107492A9936
-----------------------------------	-----------------

Classifications

ETIM 8	EC000042 - Miniature circuit breaker (MCB)
ETIM 9	EC000042 - Miniature circuit breaker (MCB)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8536 20 10
UNSPSC	39121614
eClass	V11.0 : 27141901
Object Classification Code	F

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs

