



 PRODUCT-DETAILS

ST202MTR-K6 DC

Miniature Circuit Breakers MCBs - 2P - K - 6 A



General Information

Extended Product Type	ST202MTR-K6 DC
Product ID	2CDS272566R0377
EAN	4016779111102
Catalog Description	Miniature Circuit Breakers MCBs - 2P - K - 6 A
Long Description	ST202MTR-K6 DC Miniature Circuit Breaker K-Char., 10kA, 6A, 2P

Technical

Standards	UL 1077, CSA 22.2 No. 235
Tripping Characteristic	K
Rated Voltage (U_r)	500 V DC
Rated Operational Voltage	440 V AC
Operational Voltage	acc. to IEC 60947-2 240 V AC
Rated Insulation Voltage (U_i)	Minimum 12 V AC / 12 V DC
Rated Impulse Withstand Voltage (U_{imp})	acc. to IEC/EN 60664-1 440 V
	at Sea Level 4 kV

Dielectric Test Voltage	50/60 Hz-1 min: 2 kV
Input Voltage Type	DC
Rated Current (I _n)	6 A
Rated Short-Circuit Capacity	(400 V) 10 kA
Rated Frequency (f)	50 / 60 Hz
Power Loss	3.2 W
Contact Position Indication	ON / OFF
Energy Limiting Class	3
Mechanical Endurance	20000 cycle
Number of Protected Poles	2
Number of Poles	2
Overvoltage Category	III
Tightening Torque	2.8 N·m
Screw Terminal Type	Ring-Tongue Terminal with Captive Screw
Actuator Marking	I / O
Actuator Material	Insulation Group II, Black, Sealable
Housing Material	Insulation Group I, RAL 7035
Options Provided	Suitable for traction application
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Mounting Position	any
Recommended Screw Driver	Pozidriv 2
Accessories Available	Yes
Connecting Capacity	Busbar 16 mm ²
Terminal Type	Ring-Tongue Terminals

Material Compliance

RoHS Information	9AKK108466A5762
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20220630
REACH Declaration	9AKK107492A1906
REACH Information	True - contains substances > 0.1 mass percentage
REACH Date	20240821
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Air Temperature	Operation -40 ... +75 °C Storage -40 ... +75 °C
Degree of Protection	IP20 Enclosure with Cover IP20
Pollution Degree	3
Environmental Conditions	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
Resistance to Vibrations	20 Cycles with Load 0.8 In: 5g 5 ... 150 ... 5 Hz
Resistance to Shock acc. to IEC 60068-2-27	25g 2 shocks 13 ms

Dimensions

Product Net Width	35 mm
Product Net Height	100 mm
Product Net Depth / Length	69 mm
Product Net Weight	0.25 kg
Pole Net Weight	0.125 kg
Built-In Depth (t ₂)	69 mm

Ordering

Package Level 1 Units	box 5 piece
Package Level 1 Gross Weight	1.262 kg

Certificates and Declarations

Declaration of Conformity - CE	9AKK108466A5762
Certification Agency	IEC

Installation

Instructions and Manuals	2CDS207104P0002
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	No document needed
-----------------------------------	--------------------

Classifications

ETIM 8	EC000042 - Miniature circuit breaker (MCB)
ETIM 9	EC000042 - Miniature circuit breaker (MCB)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	8536 20 10
UNSPSC	39121603
eClass	V11.0 : 27141901
IDEA Granular Category Code (IGCC)	4897 >> Miniature circuit breakers
Object Classification Code	F

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs

