



PRODUCT-DETAILS

PK48

PK48 Street light Cabinet



General Information	
Extended Product Type	PK48
Product ID	2CEA000042R2226
EAN	5703510023853
Catalog Description	PK48 Street light Cabinet
Long Description	PK48 Street light Cabinet

Environmental	
Degree of Protection	IP44

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85381000
Country of Origin	Denmark (DK)

Dimensions

Product Net Width	592 mm
Product Net Height	1116 mm
Product Net Depth / Length	222 mm
Product Net Weight	35.9 kg

Technical

Rated Insulation Voltage (U _i)	1000 V
Rated Operational Voltage	400 V
Rated Peak Withstand Current Low Voltage (I _{pk})	32 kA
Rated Short-time Withstand Current Low Voltage (I _{cw})	16 kA
Standards	IEC61439-5
Color	NCS 7020-B10G
Mounting Type	Ground mounted
Degree of Protection	IP44
Enclosure Material	Composite
Rated Current (I _n)	400 A
Rated Voltage (U _r)	500 V

Classifications

ETIM 8	EC003517 - Cable distribution cabinet
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Cable Distribution Cabinets → CDC DK Cable Distribution Cabinets → Cable Distribution Cabinets with Components

