6705-101 1/4



PRODUCT-DETAILS

6705-101

WaveLine Switch / Shutter Actuator Radio Control with extention unit with ON/OFF / venetian blind switching and lightscene control 230 V



General Information	
Extended Product Type	6705-101
Product ID	2CKA006700A0041
EAN	4011395182659
Catalog Description	WaveLine Switch / Shutter Actuator Radio Control with extention unit with ON/OFF / venetian blind switching and lightscene control 230 V
Long Description	For wireless switching of electrical loads. For driving and adjusting blinds/shutters and awnings over radio. Functions via radio control: 2gang switch, blind switch and light scene control. Functions via extension unit: 2gang switch, blind switch and send radio control telegram. Operation via conventional push button (2020 US/2021/6 UK) possible. Actuation of the extension unit (via conventional push-button) causes the output to switch and a radio control telegram to be sent. Actuation of the extension unit in 2gang switch function: An ON/OFF telegram is sent alternately. Actuation of the extension unit in blind switch function: Extension unit 1 sends an UP and extension unit 2 sends a DOWN telegram. For wall mounted transmitter Waveline 6731-xxx, 6732-xxx und 6733-xxx. For remote control WaveLINE 6780. With blind switch function: 3 minutes run time. Repeater function can be activated for extended range. For universal attachment or installation. 3 wire connection (neutral conductor required). For installation in (deep) flush-mounted boxes to German Standard DIN 49073. Controllable up to 32 transmission addresses. Send/receive frequency: 868 MHz. Free-field range: approx. 100 m.

6705-101 2/4

Installation	
Instructions and Manuals	2CKA000073B8371
Mounting Type	Flush Mounted
Type of Fastening	Clamp
Environmental Ambient Air	Operation -5 +45 °C
Tomporatura	
Temperature	
Degree of Protection	IP20
	IP20
Degree of Protection	No document needed

lechnical	
Data Sheet, Technical Information	No document needed
Number of Outputs	2
Number of Relays	2
Number of Commands	3
Number of Inputs	2
Product Range	WaveLINE
Transmission Standard	Radio Control
Options Provided	ON/OFF / venetian blind switching and lightscene control
Cable Length	0.11 m

Electrical		
Current Type	230 V AC	
Rated Voltage (U _r)	230 V	
Rated Current (In)	3 A	
Rated Frequency (f)	50 Hz	
Load Type	Electrical drives	

Design	
Surface Finishing	Untreated Matt
Material	Thermoplastic
Color	studio white

Dimensions	
Product Net Width	71 mm
Product Net Height	71 mm
Product Net Depth / Length	44 mm
Product Net Weight	66 g
Built-In Depth (t ₂)	29 mm

Material Compliance

6705-101 3/4

RoHS Information	2CKA200000E6198	
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019	
REACH Declaration	2CKA309999E9999	
REACH Information	False - does not contain substances > 0.1 mass percentage	
REACH Date	20230825	
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363	

Certificates and Declarations

Declaration of 2CKA100000E1782
Conformity - CE

Classifications

ETIM 9	EC000436 - Radio receiver
eClass	V11.0 : 27144202
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Accessories

Identifier	Description	Type Quantity		Unit Of Measure
2CKA006700A0027	WaveLine Switch Actuator Wireless with ON/OFF switching, timer and light scene control WaveLINE 230 V	6702	1	piece
2CKA006700A0029	WaveLine Universal dimming actuator Wireless with ON/OFF switching, dimming and lightscene control WaveLINE 230 V	6704	1	piece

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Wiring\ Accessories\ -\ Light\ Switch\ Ranges \rightarrow Flush\ Mounted\ Inserts \rightarrow Electronic\ Inserts$

6705-101 4/4

