



 PRODUCT-DETAILS

2/2UF2120

Fire resistance - wall cabinet, Rows: 6, 982 mm x 582 mm x 205 mm, Isolated (Class II), IP41



General Information

Extended Product Type	2/2UF2120
Product ID	2CPX040041R9999
EAN	4011617400417
Catalog Description	Fire resistance - wall cabinet, Rows: 6, 982 mm x 582 mm x 205 mm, Isolated (Class II), IP41
Long Description	Fire resistance - wall cabinet, series UF, empty cabinet, for the internal use, with Door, class of protection II (double insulated), degree of protection IP41, fire resistance 30 min tested according to , Reduce fire load 30 min in line with , Maintain functionality 30 min in line with , Impact strength IK08, Rated operational voltage 400V AC 50/60 Hz, Coated, in RAL 7035, enclosure out of non flammable material, single-leaf door, door out of non flammable material, with Swivel handle with half cylinder, door opening angle 180 degree, door hinge links, cable entry on top via fire stop cable entry, on bottom via fire stop cable entry, dimensions in mm (H x W x D): 982 x 582 x 205, Grid unit 6 GU, Overall height 2, panel width 2, Space units 144, pre-assembled for installation with Modules, Combi-Sets, CombiLine-Module on EDF-mounting frame

Technical

Flammability Hazard Rating	E30
Rated Operational Voltage	Maximum 400 V
Operational Voltage	400 V

Number of Flange Openings	2
Number of Conduit Inlets	2
Number of Rows	6
Configuration Type	pre-assembled for installation with Modules, Combi-Sets, CombiLine-Module on EDF-mounting frame
Cover Plate Type	None
Enclosure Type	Fire resistance - wall cabinet
Enclosure Type of Height	2
Mounting Type	Flush mounting
Door Type	Single
Surface Finishing	Coated
Housing Material	Other
Cover Style	with Notch
DIN Place Units	144
Meter Boards	0
RAL Number	RAL 7035 - Light Grey
Color	Light grey

Material Compliance

RoHS Information	2CPC100026X0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20240917
REACH Declaration	2CPC100005X0201
REACH Information	False - does not contain substances > 0.1 mass percentage
REACH Date	20240902
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Degree of Protection	IP41
Protection Class	Isolated (Class II)

Dimensions

Width in Number of Modular Spacings	24
Product Net Width	582 mm
Product Net Height	982 mm
Product Net Depth / Length	205 mm
Section Width	2
Product Net Weight	82 kg
Built-In Depth (t ₂)	138 mm
Thickness	Cabinet Plate 72 mm Door Plate 72 mm

Ordering

Package Level 1 Units	pack 1 piece
Package Level 1 Gross Weight	82 kg

Certificates and Declarations

Declaration of Conformity - CE	2CPC100026X0201
-----------------------------------	-----------------

Installation

Instructions and Manuals	No document needed
--------------------------	--------------------

Popular Downloads

Data Sheet, Technical Information	2CPC000001C0101 2CPC000002C0101
--------------------------------------	------------------------------------

Classifications

ETIM 8	EC000058 - Empty cabinet
ETIM 9	EC000058 - Empty cabinet
WEEE Category	Product Not in WEEE Scope
CN8	85381000
eClass	V11.0 : 27142408
Object Classification Code	U

Safety Information

Circuit Integrity	E 30
-------------------	------

Categories

Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Fire Resistant Enclosures → UF

