

PRODUCT-DETAILS

## E 91hN/32 sx

## Fuse holder



General Information	
Extended Product Type	E 91hN/32 sx
Product ID	2CSM264383R1801
EAN	8012542643838
Catalog Description	Fuse holder
Long Description	E 91HN/32 sx is a fuseholder for overcurrent and short circuit protection

Technical	
Rated Voltage (U <sub>r</sub> )	acc. To IEC 400 V
Rated Operational Voltage	400 V AC
Rated Insulation Voltage (U <sub>1</sub> )	1 kV
Rated Frequency (f)	50/60 Hz
Power Loss	at Rated Operating Conditions per Pole 3 W
Number of Protected Poles	1
Number of Poles	2

E 91hN/32 sx 2/4

Position of Neutral	Left
Terminals	
Tightening Torque	0.81.2 N·m
Fuse Type	gG and aM cylindrical fuse links
Lock Type	Padlockable
Mounting Type	DIN-Rail
Sealing Type	Sealing Wire
Material of Conductor	Copper
Options Provided	No
Recommended Screw	Pozidriv 2
Driver	
Shock and Vibration	Category 1, Class B
Withstand acc. to IEC	
61373	
Connecting Capacity	Stranded 1.510 mm <sup>2</sup>
	Rigid 1.516 mm²
Fuse Size	10x38 mm
	max. 90% at +20 °C, 50% at max. +40 °C
Rated Operational	32 A
Current AC (I <sub>e</sub> )	

Material Compliance	
RoHS Information	2CSC444001D2701
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	41640
REACH Declaration	9AKK108467A9482
REACH Information	True - contains substances > 0.1 mass percentage
REACH Date	20240429
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental	
Ambient Air Temperature	Operation -5+40 °C Storage -25+70 °C
Degree of Protection	IP20
Maximum Operating Altitude Permissible	2000 m
Resistance to Vibrations	1 mm 2 13 Hz
Resistance to Shock acc. to IEC 60068-2-27	15g 18 shocks 11 ms
Environmental Information	See RoHS Information

Dimensions	
Width in Number of Modular Spacings	1
Product Net Width	0.018 m
Product Net Height	0.085 m
Product Net Depth / Length	0.064 m
Product Net Weight	0.070 kg
Built-In Depth (t <sub>2</sub> )	64 mm

E 91hN/32 sx 3/4

Ordering	
Package Level 1 Units	box 6 piece
Package Level 1 Gross Weight	0.429 kg

Certificates and Declarations	
BV Certificate	9AKK108467A0330
CCC Certificate	9AKK108467A0341
Declaration of Conformity - CE	2CSC444001D2701
IMQ Certificate	9AKK108467A0322
Certification Agency	IMQ, BV, CCC, EAC

Installation	
Instructions and	No document needed
Manuals	

Popular Downloads	
Data Sheet, Technical	2CSC400002D0209
Information	

Classifications	
ETIM 8	EC002705 - Holder for cylindrical fuse
ETIM 9	EC002705 - Holder for cylindrical fuse
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85361050
eClass	V11.0 : 27142121
Object Classification Code	F

## **Categories**

 $Low\ Voltage\ Products\ \rightarrow\ Devices\ \rightarrow\ Cylindrical\ Fuse\ Holders\ and\ Fuse\ Switch\ Disconnectors$ 

E 91hN/32 sx 4/4

