



PRODUCT-DETAILS

DSB201M APR-C32/0.3

Residual Current Circuit Breaker with Overcurrent Protection

Product image
not available

General Information

Extended Product Type	DSB201M APR-C32/0.3
Product ID	2CSR275475R3324
Catalog Description	Residual Current Circuit Breaker with Overcurrent Protection
Long Description	DSB201M APR-C32/0.3 - RCCB with Over current protection

Technical

Standards	IS 12640-2 IEC 61009-1
Tripping Characteristic	C
Type of Residual Current	Type A
Rated Operational Voltage	240 V
Operational Voltage	110 (170 for 30mA) V
Rated Insulation Voltage (U _i)	500 V AC
Rated Impulse Withstand Voltage (U _{imp})	4 kV

Dielectric Test Voltage	2.5 kV
Rated Current (I _n)	32 A
Rated Residual Current	300 mA
Rated Short-Circuit Capacity	10000 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	7.5 kA
Rated Frequency (f)	50 Hz
Contact Position Indication	Red ON / Green OFF
Energy Limiting Class	3
Electrical Endurance	10000 cycle
Mechanical Endurance	20000 cycle
Number of Protected Poles	2
Number of Poles	1+N
Operating Characteristic	Instantaneous (APR High Immunity)
Overvoltage Category	III
Tightening Torque	2.8 N·m
Accessory Type	ALL
Actuator Type	Insulation group II, Black RAL 9005, sealable in ON-OFF positions
Housing Type	Insulation group I - II, RAL 7035
Mounting Type	DIN-Rail
Screw Terminal Type	Failsafe Bi-directional Cylinder-lift Terminal
Mounting Position	Any
Accessories Available	Yes
Number of Batteries	0
Connecting Capacity	25/25 mm ²
Wire Stripping Length	12 mm

Material Compliance

RoHS Status	No declaration needed
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Air Temperature	-25...+55 °C
Degree of Protection	Housing IP40 Terminals IP20
Pollution Degree	2
Resistance to Vibrations	20 Cycles with Load 0.8 In: 1g or 1mm 5...150...5 Hz
Resistance to Shock acc. to IEC 60068-2-27	25g 2 shocks 13 ms

Certificates and Declarations

Declaration of Conformity - CE	No declaration needed
--------------------------------	-----------------------

Installation

Instructions and
ManualsNo document needed

Popular Downloads

Data Sheet, Technical
InformationNo document needed

Classifications

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

WEEE B2C / B2B

Business To Consumer

CN8

85363010

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Circuit Breakers with Overcurrent Protection RCBO



Product image
not available