




---

 PRODUCT-DETAILS

## ACS880-01-361A-5

LV AC industrial wall-mounted single drive,  
IEC: Pn 200 kW, 361 A, 500 V, UL: Pld 300 Hp,  
361 A, 460 V (ACS880-01-361A-5)




---

**General Information**

Global Commercial Alias	ACS880-01-361A-5
Product ID	3AUA0000082215
ABB Type Designation	ACS880-01-361A-5
EAN	6438177555124

Catalog Description	LV AC industrial wall-mounted single drive, IEC: Pn 200 kW, 361 A, 500 V, UL: Pld 300 Hp, 361 A, 460 V (ACS880-01-361A-5)
---------------------	---

The ACS880-01 drives are customized to meet the particular needs of specific industries, such as oil and gas, mining, metals, chemicals, cement, power plants, material handling, pulp and paper, sawmills, marine, water and wastewater, food and beverage, and automotive. They can control a wide range of applications, including cranes, extruders, winches, winders, conveyors, mixers, compressors, centrifuges, test benches, elevators, extruders, pumps and fans.

**Long Description**

The ACS880-01 comes in one compact package for easy installation and commissioning. The drive can be installed on the wall as standard and in a cabinet as an option. The drive offering includes enclosure classes up to IP55, making it suitable for most environments and installations. ACS880-01 drives have all the essential features built-in. These features include as standard a choke for harmonic filtering as well as options like a brake chopper, EMC filter and communication protocol adapter, functional safety, external output filters and I/O extension modules.

---

## Ordering

Country of Origin	Finland (FI)
Customs Tariff Number	85044086
HS Code	850440-- Electrical transformers, static converters (for example, rectifiers) and inductors.- Static converters
Invoice Description	ACS880-01-361A-5 PN: 200 kW, IN: 361 A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

## Dimensions

Product Net Weight	95.0 kg 209.439 lb
Product Net Depth / Length	413 mm 16.260 in
Product Net Height	955 mm 37.598 in
Product Net Width	380 mm 14.961 in
Package Level 1 Depth / Length	1145 mm 45.08 in
Package Level 1 Height	654 mm 25.75 in
Package Level 1 Width	485 mm 19.09 in
Package Level 1 Units	1 case

## Technical

Number of Phases	3
Degree of Protection	IP21
Enclosure Type NEMA	Type1
Altitude	4000 m 5 ... 95
Sound dB (A)	70 dB(A)
Multiple Battery Information	Lithium Coin, CR2032, 220 mAh, 3 V, 2 pcs, 6 g
Frequency (f)	47.5 ... 63 Hz
Frame Size	R9
Input Voltage (U <sub>in</sub> )	380 ... 500 V
Mounting Type	Wall-mounted
Communication Protocol	CAN DeviceNet EtherNet/IP MODBUS Other Bus Systems PROFIsafe PROFIBUS PROFINET IO
Number of Hardware Interfaces	Industrial Ethernet 0 Other 4 Parallel 0 PROFINET 0 RS-232 0

	RS-422 0 RS-485 1 Serial TTY 0 USB 1
Includes	Control unit PC connection
Analog Inputs	2
Analog Outputs	2
Number of Digital In/Outputs	6 / 2
Output Current, Heavy-Duty Use ( $I_{HD}$ )	302 A
Output Current, Light-Overload Use ( $I_{LD}$ )	343 A
Output Current, Normal Use ( $I_n$ )	361 A
Output Power, Heavy-Duty Use ( $P_{HD}$ )	200 kW
Output Power, Light-Overload Use ( $P_{LD}$ )	200 kW
Output Power, Normal Use ( $P_n$ )	200 kW
Apparent Power Output	313 kV·A
Efficiency Level	IE2
Standby Loss	118 W
Complete Drive Module Efficiency (61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	1199 W	93.3 %	0.4 %
0/50 %	1777 W	94.9 %	0.6 %
0/100 %	3190 W	95.3 %	1.0 %
50/25 %	1277 W	96.5 %	0.4 %
50/50 %	1906 W	97.3 %	0.6 %
50/100 %	3658 W	97.4 %	1.2 %
90/50 %	2224 W	98.2 %	0.7 %
90/100 %	4781 W	98.1 %	1.5 %

Temperature Rating	Maximum 40 °C Minimum -15 °C
--------------------	---------------------------------

### Technical UL

Output Current, Heavy-Duty Use (UL)	302 A
Output Current, Light-Overload Use (UL)	361 A
Output Current, Normal Use (UL)	- A
Output Power, Heavy-Duty Use (UL)	250 Hp
Output Power, Light-Overload Use (UL)	300 Hp

---

### Classifications

---

ETIM 8	EC001857 - Frequency converter =< 1 kV
ETIM 9	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

---

---

### Environmental

---

SCIP	f3069b98-085a-411d-9aa2-a35fb9711497 Finland (FI)
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

---

---

### Additional Information

---

Product Name	Frequency converter
--------------	---------------------

---

---

### Categories

---

Drives → Low Voltage AC Drives → Industrial Drives → ACS880 Single Drives → ACS880-01 - Wall-mounted single drive

