




---

 PRODUCT-DETAILS

## ACH580-BCR-07A5-2+B056

HVAC packaged drive with e-clipse bypass and circuit breaker disconnect US, UL: Pld 2 Hp, 7.5 A (ACH580-BCR-07A5-2+B056)




---

**General Information**

Global Commercial Alias	ACH580-BCR-07A5-2+B056
Product ID	3AUA0000227519
ABB Type Designation	ACH580-BCR-07A5-2+B056
EAN	6438177528821
Catalog Description	HVAC packaged drive with e-clipse bypass and circuit breaker disconnect US, UL: Pld 2 Hp, 7.5 A (ACH580-BCR-07A5-2+B056)
Long Description	The ACH580 with ABB E-Clipse bypass has an integrated UL (NEMA) Type 1, 12 or 3R enclosure with a bypass motor starter and is available from 1 to 350 hp at 230/460/575 V. The ACH580 with ABB E-Clipse bypass provides an input disconnect switch or circuit breaker with door mounted and interlocked switch (padlockable in the OFF position), a bypass starter, electronic motor overload protection, a door mounted control panel with graphical display for local control, provisions for external control connections, and serial communications capability

---

**Ordering**

Country of Origin	United States (US)
Customs Tariff Number	85044080
Made To Order	No

Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

---

## Dimensions

Product Net Weight	0 kg
--------------------	------

---

## Technical

Number of Phases	3
Degree of Protection	IP55
Enclosure Type NEMA	Type12
Frequency (f)	50/60 Hz
Input Voltage (U <sub>in</sub> )	208 ... 240 V

---

## Technical UL

Output Current, Light-Overload Use (UL)	7.5 A
Output Power, Light-Overload Use (UL)	2 Hp

---

## Additional Information

Product Name	AC Drive
--------------	----------

---

## Categories

Drives → Low Voltage AC Drives → Industry-Specific Drives → Drives for HVAC → ACH580-BCR - HVAC packaged drive with e-clipse bypass and circuit breaker disconnect US

