




---

 PRODUCT-DETAILS

## ACS880-31-072A-3

LV AC industrial wall-mounted low harmonic single drive, IEC: Pn 37 kW, 72 A, 400 V (ACS880-31-072A-3)




---

**General Information**

Global Commercial Alias	ACS880-31-072A-3
Product ID	3AXD50000121137
ABB Type Designation	ACS880-31-072A-3
EAN	6438177548249

Catalog Description	LV AC industrial wall-mounted low harmonic single drive, IEC: Pn 37 kW, 72 A, 400 V (ACS880-31-072A-3)
---------------------	--

## Long Description

The ACS880-31 drives are customized to meet the particular needs of specific industries, such as oil and gas, mining, metals, chemicals, cement, power plants, material handling, pulp and paper, sawmills, marine, water and wastewater, food and beverage, and automotive. They can control a wide range of applications, including cranes, extruders, winches, winders, conveyors, mixers, compressors, centrifuges, test benches, elevators, extruders, pumps and fans. The compact ACS880-31 ultra-low harmonic drive produces exceptionally low harmonic content and exceeds the requirements set by low harmonic recommendations. The drive includes an active supply unit and integrated low harmonic line filter, meaning there is no need for external filters, multi-pulse arrangements or special transformers. Other features include output voltage boost and power factor correction.

---

**Ordering**

Country of Origin	Finland (FI)
Customs Tariff Number	85044086
HS Code	850440-- Electrical transformers, static converters (for example, rectifiers) and inductors.- Static converters
Invoice Description	ACS880-31-072A-3 PN: 37 kW, IN: 72 A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

## Dimensions

Product Net Weight	61 kg 134.482 lb
Product Net Depth / Length	382 mm 15.039 in
Product Net Height	771 mm 30.354 in
Product Net Width	252 mm 9.921 in
Package Level 1 Depth / Length	992 mm 39.055 in
Package Level 1 Height	598 mm 23.543 in
Package Level 1 Width	400.0 mm 15.748 in
Package Level 1 Units	1 case

## Technical

Number of Phases	3
Degree of Protection	IP21
Enclosure Type NEMA	Type1
Altitude	4000 m 5 ... 95
Power Factor	1.0
Sound dB (A)	71 dB(A)
Multiple Battery Information	Lithium Coin, CR2032, 220 mAh, 3 V, 2 pcs, 6 g
Frequency (f)	47.5 ... 63 Hz
Frame Size	R6
Input Voltage (U <sub>in</sub> )	380 ... 415 V
Mounting Type	Wall-mounted
Communication Protocol	CAN DeviceNet EtherNet/IP MODBUS Other Bus Systems PROFIsafe PROFIBUS PROFINET IO TCP/IP
Number of Hardware Interfaces	Industrial Ethernet 0 Other 6 Parallel 0 PROFINET 0 RS-232 0

	RS-422 0 RS-485 1 Serial TTY 0 USB 1
Includes	Control unit PC connection
Analog Inputs	2
Analog Outputs	2
Number of Digital In/Outputs	6 / 2
Output Current, Heavy-Duty Use ( $I_{HD}$ )	61 A
Output Current, Light-Overload Use ( $I_{LD}$ )	68 A
Output Current, Normal Use ( $I_n$ )	72 A
Output Power, Heavy-Duty Use ( $P_{HD}$ )	30 kW
Output Power, Light-Overload Use ( $P_{LD}$ )	37 kW
Output Power, Normal Use ( $P_n$ )	37 kW
Apparent Power Output	50 kV·A
Efficiency Level	IE2
Standby Loss	51 W
Complete Drive Module Efficiency (61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	347 W	88.8 %	0.7 %
0/50 %	446 W	92.3 %	0.9 %
0/100 %	711 W	93.7 %	1.4 %
50/25 %	384 W	93.5 %	0.8 %
50/50 %	524 W	95.3 %	1.1 %
50/100 %	902 W	95.9 %	1.8 %
90/50 %	661 W	96.7 %	1.3 %
90/100 %	1447 W	96.3 %	2.9 %

Temperature Rating Maximum +55 °C  
Minimum -15 °C

Ecodesign Exemption Energy efficiency data is not provided for the drive. The low-harmonic drives are exempt from the EU ecodesign requirements (Regulation EU/2019/1781, §2.3.d).

### Classifications

ETIM 8	EC001857 - Frequency converter =< 1 kV
ETIM 9	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

### Environmental

SCIP fcdc24ef-6177-4a20-9ff6-4fd916600fd0 Finland (FI)

WEEE Category

4. Large Equipment (Any External Dimension More Than 50 cm)

---

### Additional Information

Product Name

Frequency converter

---

### Categories

Drives → Low Voltage AC Drives → Industrial Drives → ACS880 Single Drives → ACS880-31 - Wall-mounted low harmonic single drive

Drives → Services → Spares and Consumables → Parts

