



PRODUCT-DETAILS

3GBP286220-AXG

(3GBP286220-AXG)



General Information

Product ID	3GBP286220-AXG
ABB Type Designation	M3BP 280SMB 12
Catalog Description	(3GBP286220-AXG)

Ordering

ABB Type Designation	M3BP 280SMB 12
Invoice Description	M3BP 280SMB 12
Product Name	3-Phase squirrel cage motor
Product Type	3BP2_M3BP_IE2_CI
Made To Order	No
Minimum Order Quantity	1 piece
Selling Unit of Measure	piece
Country of Origin	Finland (FI) China (CN) Poland (PL)
Customs Tariff Number	85015230

Electrical

Electrical Data

	Temp Class	Speed
	--	500 r/min
Temperature Class Default	--	
Altitude		1000 m
Ambient Temperature		40 °C
IC Class		IC411
IP Class		IP55
Insulation Class		ICLF
Direction of Rotation		Both sides
Number of Poles (High)		12
Two Speed Motor		No
Type of Duty		S1
Voltage Code		X

Mechanical

Frame Material	Cast Iron
Frame Size	280
Bearing	6316/C3
Bearing NDE	6316/C3
IM Class	IMB3 IM1001
Terminator Box Location	D-End top

Dimensions

Package Level 1 Units	1 pallet (lift)
Product Net Weight	645 kg
Gross Weight	665 kg

Environmental

WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
SCIP	54c45c7b-7581-40ab-b615-c1dcb277d8a7 Finland (FI)

Classifications

UNSPSC	26101100
--------	----------

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Cast Iron Motors

