



 PRODUCT-DETAILS

3GJA132101-BDD

M2JAX 132S4A

General Information

Product ID	3GJA132101-BDD
ABB Type Designation	M2JAX132S4A
Catalog Description	M2JAX 132S4A

Additional Information

ABB Type Designation	M2JAX132S4A
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	China (CN)
Customs Tariff Number	85059090
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Torque	IS/IN
D	T4	50 Hz	380-400 V	5.50 kW	1450 r/min	10.78 A	0.840	36.22 N·m	7.50
Y	T4	50 Hz	660-690 V	5.50 kW	1450 r/min	6.25 A	0.840	36.22 N·m	7.50
D	T4	60 Hz	460 V	6.33 kW					

Frame Material	Cast Iron
Frame Size	132
Gross Weight	95 kg
IC Class	IC411
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2JAX 132S4A
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4

Order Multiple	1 piece
Product Name	3 PHASE
Product Net Weight	92 kg
Product Type	2JAX_M2JAX_IE2_Flameproof_Ex_d_motor
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Temperature Class Default	T4
Temperature Rise	80 K
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)