




---

 PRODUCT-DETAILS

# 3GSE201420-BDACN

## M2SE 200MLB2

---

**General Information**

Product ID	3GSE201420-BDACN
ABB Type Designation	M2SE 200MLB2
Catalog Description	M2SE 200MLB2

---

**Additional Information**

ABB Type Designation	M2SE 200MLB2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6312/C4
Bearing NDE	6209/C4
Country of Origin	China (CN)
Customs Tariff Number	85015100
Direction of Rotation	Both sides

**Electrical Data**

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	--	50 Hz	380 V	37.00 kW	2943 r/min	66.80 A	0.910	92.50 %	120.00 N-m	7.60
Y	--	50 Hz	660 V	37.00 kW	2943 r/min	38.50 A	0.910	92.50 %	120.00 N-m	7.60
D	--	50 Hz	400 V	37.00 kW	2951 r/min	64.20 A	0.900	92.50 %	120.00 N-m	8.40

Frame Size	200
Gross Weight	229 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 92.5 % Partial Load (75%) 92.5 % Partial Load (50%) 92.1 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLH

Invoice Description	M2SE 200MLB2
Lubrication	Regreasable
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	229 kg
Product Type	CSE2__M2SE_IE2_Smoke_extraction_motor
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Shanghai, China
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	Product Not in WEEE Scope