




---

 PRODUCT-DETAILS

# 3GSE202410-ADACN

## M2SE 200MLA4

---

**General Information**

Product ID	3GSE202410-ADACN
ABB Type Designation	M2SE 200MLA4
Catalog Description	M2SE 200MLA4

---

**Additional Information**

ABB Type Designation	M2SE 200MLA4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6312/C4
Bearing NDE	6209/C4
Country of Origin	China (CN)
Customs Tariff Number	85015100
Direction of Rotation	Both sides

**Electrical Data**

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	--	50 Hz	380 V	30.00 kW	1471 r/min	58.80 A	0.840	92.30 %	193.60 N-m	6.50
Y	--	50 Hz	660 V	30.00 kW	1471 r/min	33.80 A	0.840	92.30 %	193.60 N-m	6.50
D	--	50 Hz	400 V	30.00 kW	1476 r/min	57.90 A	0.810	92.30 %	193.60 N-m	6.80

Frame Size	200
Gross Weight	222 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 92.3 % Partial Load (75%) 92.4 % Partial Load (50%) 92.0 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLH

Invoice Description	M2SE 200MLA4
Lubrication	Regreasable
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	222 kg
Product Type	CSE2__M2SE_IE2_Smoke_extraction_motor
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Shanghai, China
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	Product Not in WEEE Scope