



 PRODUCT-DETAILS

3GSE352230-BDACN

M2SE 355SMC4

General Information

Product ID	3GSE352230-BDACN
ABB Type Designation	M2SE 355SMC4
Catalog Description	M2SE 355SMC4

Additional Information

ABB Type Designation	M2SE 355SMC4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6322/C4
Bearing NDE	6316/C4
Country of Origin	China (CN)
Customs Tariff Number	85015100
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	--	50 Hz	380 V	355.00 kW	1485 r/min	652.00 A	0.870	95.10 %	2282.25 N-m	6.10
Y	--	50 Hz	660 V	355.00 kW	1485 r/min	375.00 A	0.870	95.10 %	2282.25 N-m	6.10
D	--	50 Hz	400 V	355.00 kW	1487 r/min	619.00 A	0.870	95.10 %	2279.81 N-m	6.80

Frame Size	355
Gross Weight	1669 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 95.1 % Partial Load (75%) 95.2 % Partial Load (50%) 94.6 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLH

Invoice Description	M2SE 355SMC4
Lubrication	Regreasable
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	1669 kg
Product Type	CSE2__M2SE_IE2_Smoke_extraction_motor
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Shanghai, China
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	Product Not in WEEE Scope