



 PRODUCT-DETAILS

3GSE353230-BDACN

M2SE 355SMC6

General Information

Product ID	3GSE353230-BDACN
ABB Type Designation	M2SE 355SMC6
Catalog Description	M2SE 355SMC6

Additional Information

ABB Type Designation	M2SE 355SMC6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6322/C4
Bearing NDE	6316/C4
Country of Origin	China (CN)
Customs Tariff Number	85015100
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	--	50 Hz	380 V	250.00 kW	990 r/min	470.00 A	0.850	95.00 %	2411.60 N-m	5.60
Y	--	50 Hz	660 V	250.00 kW	990 r/min	271.00 A	0.850	95.00 %	2411.60 N-m	5.60
D	--	50 Hz	400 V	250.00 kW	991 r/min	447.00 A	0.850	95.00 %	2408.76 N-m	6.30

Frame Size	355
Gross Weight	1609 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 95.0 % Partial Load (75%) 95.3 % Partial Load (50%) 95.0 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLH

Invoice Description	M2SE 355SMC6
Lubrication	Regreasable
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	1609 kg
Product Type	CSE2__M2SE_IE2_Smoke_extraction_motor
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Shanghai, China
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	Product Not in WEEE Scope