

PRODUCT-DETAILS

1MB21212BC114AG3

No Description Available

General Information

Global Commercial Alias	1MB21212BC114AG3
Product ID	7B1MB21212BC114AG3
ABB Type Designation	MOTOR,7.5,1200,XP100,230/460,254T
Catalog Description	No Description Available

Additional Information

ABB Type Designation	MOTOR,7.5,1200,XP100,230/460,254T
Ambient Temperature	40 °C
Bearing	6309, Ball
Bearing NDE	6309
Brake Present	No
Brand / Label	ABB NEMA Motors
Catalog Number	1MB21212BC114AG3
Country of Origin	Mexico (MX)
Customs Tariff Number	8501520400
Drive End Flange Type	Standard
Efficiency Level	Premium Efficiency (NEMA 12-12)
Electrical Data	

Current

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

Enclosure Type	TEFC
Explosion Proof Group	Class I, Group C & D, Class II, Group F & G



Freq

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

Power

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

Speed

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

Voltage

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

Class	
Frame Material	Cast Iron
Frame Size	Undefined
Global Commercial Alias	1MB21212BC114AG3
Gross Volume	2.706 hl
Gross Weight	135 lb
IP Class	IP65
Insulation Class	F
Made To Order	No
Minimum Order Quantity	1 piece
Motor Base Type	Foot Mounted
Motor Frame Size	254T
Mounting Orientation	Horizontal
Mounting Position	F1
NEMA Design Code	B
Number of Phases	3
Number of Poles	6
Number of Poles (High)	6
Number of Speeds	single_speed
Order Multiple	1 piece
Output Power	7.5 Hp 5 Hp
Power Factor	77.2 %
Product Name	LVM Explosion Proof Motors - GDL
Product Net Depth / Length	0 in
Product Net Height	0 in
Product Net Weight	129 lb
Product Net Width	0 in
Product Type	Undefined
Quote Only	No
Rated Current (I _n)	17.24 A 28.62 A 10 A
Rated Efficiency	91.0 %
Rated Speed	984 r/min 1175 r/min
Selling Unit of Measure	piece
Service Factor	1.15
Standards	NEMA
Starting of Motor	Direct on line
Stocked At (Warehouses)	Fort Smith Ar, United States Tlajomulco de Zuniga, Mexico
	1000 r/min 1200 r/min
Temperature Class	T3C
Type of Duty	Continuous
Voltage Rating	200 V 230 V 400 V 460 V

