PRODUCT-DETAILS

1MB21212CC216AG3 No Description Available

General Information	
Global Commercial Alias	1MB21212CC216AG3
Product ID	7B1MB21212CC216AG3
ABB Type Designation	MOTOR,20,1200,XP100,230/460,286T
Catalog Description	No Description Available

ABB Type Designation	MOTOR,20,1200,XP100,230/460,286T	
Ambient Temperature	40 °C	
Bearing	6310, Bal	
Bearing NDE	6310	
Brake Present	Nc	
Brand / Label	ABB NEMA Motor	
Catalog Number	1MB21212CC216AG3	
Country of Origin	Mexico (MX)	
Customs Tariff Number	8501520400	
Drive End Flange Type	Standard	
Efficiency Level	Premium Efficiency (NEMA 12-12)	

Electrical Data

Current
An error has occurred while processing HtmlTextBox ": The expression contains undefined function call GetListItemValue().
An error has occurred while processing HtmlTextBox ": The expression contains undefined function call GetListItemValue().
An error has occurred while processing HtmlTextBox ": The expression contains undefined function call GetListItemValue().
An error has occurred while processing HtmlTextBox ": The expression contains undefined function call GetListItemValue().

© 2024 ABB. All rights reserved.

Class I, Group C & D, Class II, Group F & G

2024/10/26

Subject to change without notice



Freq	
An error has occurred while processing HtmlTextBox ": The expression contains undefined function call GetListItemValue().	
An error has occurred while processing HtmlTextBox ": The expression contains undefined function call GetListItemValue().	
An error has occurred while processing HtmlTextBox ": The expression contains undefined function call GetListItemValue().	
An error has occurred while processing HtmlTextBox ": The expression contains undefined function call GetListItemValue().	

Power		
An error has occurred while processing HtmlTextBox ": The expression contains undefined function call GetListItemValue().		
An error has occurred while processing HtmlTextBox ": The expression contains undefined function call GetListItemValue().		
An error has occurred while processing HtmlTextBox ": The expression contains undefined function call GetListItemValue().		
An error has occurred while processing HtmlTextBox ": The expression contains undefined function call GetListItemValue().		

Speed		
An error has occurred while processing HtmlTextBox ": The expression contains undefined function call GetListItemValue().		
An error has occurred while processing HtmlTextBox ": The expression contains undefined function call GetListItemValue().		
An error has occurred while processing HtmlTextBox ": The expression contains undefined function call GetListItemValue().		
An error has occurred while processing HtmlTextBox ": The expression contains undefined function call GetListItemValue().		

Voltage	
An error has occurred while processing HtmlTextBox ": The expression contains undefined function call GetListItemValue().	
An error has occurred while processing HtmlTextBox ": The expression contains undefined function call GetListItemValue().	
An error has occurred while processing HtmlTextBox ": The expression contains undefined function call GetListItemValue().	
An error has occurred while processing HtmlTextBox ": The expression contains undefined function call GetListItemValue().	

Class		
Frame Material	Cast Iron	
Frame Size	Undefined	
Global Commercial Alias	1MB21212CC216AG3	
Gross Volume	0.512 m³	
Gross Weight	241 lb	
IP Class	IP65	
Insulation Class	F	
Made To Order	Nc	
Minimum Order Quantity	1 piece	
Motor Base Type	Foot Mounted	
Motor Frame Size	286T	
Mounting Orientation	Horizontal	
Mounting Position	F1	
NEMA Design Code	В	
Number of Phases	3	
Number of Poles	6	
Number of Poles (High)	6	
Number of Speeds		
Order Multiple	1 piece	
Output Power	20 Hp	
	15 Hp	
Power Factor	76 %	
Product Name	LVM Explosion Proof Motors - GDL	
Product Net Depth /	0 in	
Length		
Product Net Height	0 in	
Product Net Weight	230 lb	
Product Net Width	0 in	
Product Type	Undefined	
Quote Only	Nc	
Rated Current (I _n)	48.22 A 54 A	
	24.11 A	
	27 A	
Rated Efficiency	91.7 %	
Rated Speed	985 r/min	
	1180 r/min	
Selling Unit of Measure	piece	
Service Factor	1.15	
Standards	NEMA	
Starting of Motor	Direct on line	
Stocked At	Fort Smith Ar, United States	
(Warehouses)	Tlajomulco de Zuniga, Mexico	
	1000 r/min 1200 r (min	
	1200 r/min	
Temperature Class	T3C	
Type of Duty	Continuous	
Voltage Rating	200 V 230 V	
	400 V	
	460 V	

2024/10/26

2024/10/26

2024/10/26

10/1