

PRODUCT-DETAILS

1PC65215EA812AK1

No Description Available

General Information

Global Commercial Alias	1PC65215EA812AK1
Product ID	7B1PC65215EA812AK1
ABB Type Designation	MOTOR,500,3600,DP200,460,5011S,NP
Catalog Description	No Description Available

Additional Information

ABB Type Designation	MOTOR,500,3600,DP200,460,5011S,NP
Ambient Temperature	40 °C
Bearing	6316
Bearing NDE	6316
Brake Present	No
Brand / Label	ABB NEMA Motors
Catalog Number	1PC65215EA812AK1
Country of Origin	Mexico (MX)
Customs Tariff Number	8501530400
Drive End Flange Type	Standard
Efficiency Level	Premium Efficiency (NEMA 12-12)
Electrical Data	

Current

An error has occurred while processing HtmlTextBox "
The expression contains undefined function call GetListItemValue().

Enclosure Type	TEFC
Explosion Proof Group Class	Class I, Group A, B, C & D
Frame Material	Iron
Frame Size	Undefined
Global Commercial Alias	1PC65215EA812AK1
Gross Volume	2.856 m ³
Gross Weight	2149 lb
IP Class	IP55



Freq

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

Speed

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

Voltage

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

Insulation Class	H
Made To Order	No
Minimum Order Quantity	1 piece
Motor Base Type	Foot Mounted
Motor Frame Size	5011S
Mounting Orientation	Horizontal
Mounting Position	F1
NEMA Design Code	B
Number of Phases	3
Number of Poles	2
Number of Poles (High)	2
Number of Speeds	single_speed
Order Multiple	1 piece
Output Power	500 Hp
Power Factor	90.8 %
Product Name	Definite Purpose
Product Net Depth / Length	0 in
Product Net Height	0 in
Product Net Weight	2086 lb
Product Net Width	0 in
Product Type	Undefined
Quote Only	No
Rated Current (I _n)	535 A
Rated Efficiency	96.5 %
Rated Speed	3585 r/min
Selling Unit of Measure	piece
Service Factor	1.15
Shaft Grounding	Mounting Provisions Only
Standards	NEMA
Starting of Motor	Direct on line
Stocked At (Warehouses)	Fort Smith Ar, United States Tlajomulco de Zuniga, Mexico
	3600 r/min
Temperature Class	T3
Type of Duty	Continuous
Voltage Rating	460 V

