




---

 PRODUCT-DETAILS

# CDRX14124T-5

## Explosion Proof Drill Rig Duty 1 Hp 575 V (CDRX14124T-5)




---

**General Information**

Global Commercial Alias	CDRX14124T-5
Product ID	7BCDRX14124T-5
ABB Type Designation	1HP,3450RPM,3PH,60HZ,143TC,XPFC,F1
Catalog Description	Explosion Proof Drill Rig Duty 1 Hp 575 V (CDRX14124T-5)

---

**Ordering**

ABB Type Designation	1HP,3450RPM,3PH,60HZ,143TC,XPFC,F1
Invoice Description	1HP,3450RPM,3PH,60HZ,143TC,XPFC,F1
Product Name	Explosion Proof Drill Rig Duty
Product Type	Undefined
Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Selling Unit of Measure	piece
Country of Origin	United States (US)
Customs Tariff Number	85015100
Stocked At (Warehouses)	China Alabama, United States Alaska, United States

Medium Description	Explosion Proof Drill Rig Duty, 1 HP, 3600 RPM, Frame Size 143Tc, C-Face Mounting, 3 Phase, XPFC Enclosure, 575 V, 60 Hz (CDRX14124T
Short Description	1 HP, 3600 RPM, Frame Size 143Tc, C-Face, 3 PH, XPFC, 575 V

---

## Electrical

---

### Electrical Data

Current	Freq	Power	Speed	Voltage
1.1 A	60 Hz	1 Hp	3450 r/min	575 V

Frequency (f)	60 Hz
Output Power	1 Hp
Ambient Temperature	40 °C
Insulation Class	F
Number of Poles (High)	2
Type of Duty	Continuous

---

## Mechanical

---

Frame Material	Steel
Frame Size	143

---

## Dimensions

---

Product Net Depth / Length	19.375 in
Product Net Height	13.123 in
Product Net Width	13.75 in
Product Net Weight	41 lb
Gross Weight	41 lb

---

## Classifications

---

Standards	NEMA
-----------	------

---

## Categories

---

Motors and Generators → Motors and Generators for Explosive Atmospheres → Explosion Proof Motors → Drill Rig Duty, 1.15 SF Motors

