



 PRODUCT-DETAILS

CXT3302TS

No Description Available



General Information

Global Commercial Alias	CXT3302TS
Product ID	7BCXT3302TS
ABB Type Designation	30HP,3525RPM,3PH,60HZ,286TSC,1048M,
Catalog Description	No Description Available

Additional Information

ABB Type Designation	30HP,3525RPM,3PH,60HZ,286TSC,1048M,
Ambient Temperature	40 °C
Bearing	6311
Bearing NDE	6309
Brake Present	No
Brand / Label	Baldor-Reliance®
Catalog Number	CXT3302TS
Certification Agency	CCSA US CSA EEV NEMA_PREMIUM UR
Country of Origin	United States (US)
Customs Tariff Number	85015230

Drive End Flange Type	C-Face			
Efficiency Level	Premium Efficiency (NEMA 12-12)			
Electrical Data				
	Current	Freq	Power	Speed
	68 A	60 Hz	30 Hp	3525 r/min
	34 A	60 Hz	30 Hp	3525 r/min
				Voltage
				230 V
				460 V
Enclosure Type	TEFC			
Explosion Proof Group Class	Class I, Group A, B, C & D			
Frame Material	Iron			
Frame Size	Undefined			
Global Commercial Alias	CXT3302TS			
Gross Volume	16254 in ³			
Gross Weight	417 lb			
Insulation Class	F			
Made To Order	No			
Medium Description	Frame Size 286Tsc, C-Face Mounting, 3 Phase, TEFC Enclosure, (CXT3302TS)			
Minimum Order Quantity	1 piece			
Motor Base Type	Foot Mounted			
Motor Frame Size	286TSC			
Mounting Orientation	Horizontal			
Mounting Position	F1			
NEMA Design Code	B			
Number of Phases	3			
Number of Poles	2			
Number of Poles (High)	2			
Number of Speeds	single speed			
Order Multiple	1 piece			
Output Power	30 Hp			
Power Factor	90 %			
Product Name	LV Severe Duty Motors			
Product Net Depth / Length	31.5 in			
Product Net Height	21.5 in			
Product Net Weight	417 lb			
Product Net Width	24 in			
Product Type	Undefined			
Quote Only	No			
Rated Current (I _n)	68 A 34 A			
Rated Efficiency	91.70 %			
Rated Speed	3525 r/min			
Selling Unit of Measure	piece			
Service Factor	1.15			
Shaft Diameter	1.63 in			
Short Description	Frame Size 286Tsc, C-Face, 3 PH, TEFC,			
Standards	NEMA			
Starting of Motor	Direct on line			
Stocked At (Warehouses)	China Alabama, United States Alaska, United States			
	3600 r/min			
Temperature Class	T3			
Type of Duty	Continuous			
Voltage Rating	230 V 460 V			

