



 PRODUCT-DETAILS

EM3764T-BG

Shaft Ground 3 Hp 230 V (EM3764T-BG)



General Information

Global Commercial Alias	EM3764T-BG
Product ID	7BEM3764T-BG
ABB Type Designation	3HP,1165RPM,3PH,60HZ,213T,TEFC,F1
Catalog Description	Shaft Ground 3 Hp 230 V (EM3764T-BG)

Additional Information

ABB Type Designation	3HP,1165RPM,3PH,60HZ,213T,TEFC,F1
Ambient Temperature	40 °C
Bearing	6307 Ball
Bearing NDE	6307 Ball
Brake Present	No
Brand / Label	Baldor-Reliance
Catalog Number	EM3764T-BG
Certification Agency	CSA CSA EEV UR

Country of Origin	United States (US)
Customs Tariff Number	85015220
Dimension Diagram	07LYN555
Drive End Flange Type	Standard
Duty Time	60 Min
ETIM 7	EC001851 - Electric motor
Efficiency Level	Premium Efficiency (NEMA 12-12)

Electrical Data

Current	Freq	Power	Speed	Voltage
9 A	60 Hz	3 Hp	1165 r/min	230 V
4.5 A	60 Hz	3 Hp	1165 r/min	460 V

Enclosure Type	TEFC
Frame Material	Iron
Frame Size	213
Frequency (f)	60 Hz
Global Commercial Alias	EM3764T-BG
Gross Volume	9144.346 in ³
Gross Weight	211 lb
IDEA Granular Category Code (IGCC)	1318 >> Heating and cooling system motor AC
Insulation Class	H
Invoice Description	3HP,1165RPM,3PH,60HZ,213T,TEFC,F1
Made To Order	No
Medium Description	Shaft Ground, 3 HP, 1200 RPM, Frame Size 213T, Standard Mounting, 3 Phase, TEFC Enclosure, 230/460 V, 60 Hz (EM3764T-BG)
Minimum Order Quantity	1 piece
Motor Base Type	Foot Mounted
Motor Frame Size	213T
Motor Frame Suffix	T
Mounting Orientation	Horizontal
Mounting Position	F1
NEMA Design Code	B
Number of Phases	3
Number of Poles	6
Number of Poles (High)	6
Number of Speeds	Single Speed
Order Multiple	1 piece
Output Power	3 Hp
Power Factor	71 %
Product Name	Shaft Ground
Product Net Depth / Length	28.625 in
Product Net Height	17.625 in
Product Net Weight	211 lb
Product Net Width	18.125 in
Product Type	Undefined
Quote Only	No
Rated Current (I _n)	9 A 4.5 A
Rated Efficiency	89.50 %
Rated Speed	1165 r/min
Selling Unit of Measure	piece
Service Factor	1.15
Shaft Diameter	1.38 in

Shaft Grounding	Shaft Grounding
Short Description	3 HP, 1200 RPM, Frame Size 213T, Standard, 3 PH, TEFC, 230/460 V
Standards	NEMA
Starting of Motor	Direct On Line
Stocked At (Warehouses)	China Alabama, United States Alaska, United States
Type of Duty	1200 r/min Continuous
UNSPSC	26101105
Voltage Rating	230 V 460 V

Categories

Motors and Generators → NEMA Low Voltage AC Motors → HVAC Motors → Shaft Grounding Motors

