M2516TX 1/3



PRODUCT-DETAILS

## M2516TX

## 25HP,3510RPM,3PH,60HZ,256T,3934M,OPSB,F



General Information		
Global Commercial Alias	M2516TX	
Product ID	7BM2516TX	
ABB Type Designation	25HP,3510RPM,3PH,60HZ,256T,3934M,OP	
Catalog Description	25HP,3510RPM,3PH,60HZ,256T,3934M,OPSB,F1	

25HP,3510RPM,3PH,60HZ,256T,3934M,OP	
40 °C	
Baldor-Reliance	
CSA UR	
United States (US)	
85015230	
Energy Efficiency (NEMA 12-11) IE2 Not Regulated / Exempt	

M2516TX 2/3

Current	Freq	Power	Speed	Voltage
58 A	60 Hz	25 Hp	3510 r/min	230 V
29 A	60 Hz	25 Hp	3510 r/min	460 V

OPSB	Enclosure Type
Steel	Frame Material
Undefined	Frame Size
M2516TX	Global Commercial Alias
95.254 kg	Gross Weight
25HP,3510RPM,3PH,60HZ,256T,3934M,OPSB,F1	Invoice Description
No	Made To Order
Frame Size 256T, 3 Phase, OPSB Enclosure, (M2516TX)	Medium Description
1 piece	Minimum Order Quantity
Rigid	Motor Base Type
256T	Motor Frame Size
В	NEMA Design Code
3	Number of Phases
Single Speed	Number of Speeds
1 piece	Order Multiple
GP 3PH Open	Product Name
O in	Product Net Depth / Length
0 in	Product Net Height
95.254 kg	Product Net Weight
0 in	Product Net Width
Undefined	Product Type
No	Quote Only
piece	Selling Unit of Measure
1.15	Service Factor
Frame Size 256T, 3 PH, OPSB,	Short Description
NEMA	Standards
Direct On Line	Starting of Motor
China Alabama, United States Alaska, United States	Stocked At (Warehouses)
26101112	UNSPSC

M2516TX 3/3

