
 PRODUCT-DETAILS

VFSFWDM3538-E

Washdown Motor 0.5 Hp 208 V (VFSFWDM3538-E)



General Information

Global Commercial Alias	VFSFWDM3538-E
Product ID	7BVFSFWDM3538-E
ABB Type Designation	.5HP,1770RPM,3PH,60HZ,56C,3512M,TEF
Catalog Description	Washdown Motor 0.5 Hp 208 V (VFSFWDM3538-E)

Additional Information

ABB Type Designation	.5HP,1770RPM,3PH,60HZ,56C,3512M,TEF
Ambient Temperature	40 °C
Bearing	6205 Ball
Bearing NDE	6205 Ball
Brake Present	No
Brand / Label	Baldor-Reliance
Catalog Number	VFSFWDM3538-E
Certification Agency	CSA UR



Country of Origin	United States (US)
Customs Tariff Number	85015100
Dimension Diagram	35LYE4649
Drive End Flange Type	C-Face
Duty Time	60 Min
ETIM 7	EC001851 - Electric motor
Efficiency Level	2015 Small Motor Standard Not Regulated / Exempt Undefined Efficiency

Electrical Data

Current

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

Enclosure Type	TEFC
Frame Material	Stainless Steel
Frame Size	56
Frequency (f)	60 Hz
Global Commercial Alias	VFSFWD3538-E
Gross Volume	3496.049 in ³
Gross Weight	35 lb
IDEA Granular Category Code (IGCC)	1325 >> General purpose motor AC
Insulation Class	H
Invoice Description	.5HP,1770RPM,3PH,60HZ,56C,3512M,TEFC,F1
Made To Order	No
Medium Description	Food Safe Washdown, 0.5 HP, 1800 RPM, Frame Size 56C, C-Face Mounting, 3 Phase, TEFC Enclosure, 208-230/460 V, 60 Hz (VFSFWD3538-E)
Minimum Order Quantity	1 piece
Motor Base Type	Footless
Motor Frame Size	56C
Motor Frame Suffix	C
Mounting Orientation	Horizontal
Mounting Position	F1
NEMA Design Code	B
Number of Phases	3
Number of Poles	4
Number of Poles (High)	4
Number of Speeds	Single Speed
Order Multiple	1 piece
Output Power	0.5 Hp
Power Factor	65 %
Product Name	Food Safe Washdown
Product Net Depth / Length	19.375 in
Product Net Height	13.123 in
Product Net Weight	35 lb
Product Net Width	13.75 in
Product Type	Undefined
Quote Only	No

Freq

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

Power

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

Speed

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

Voltage

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

Rated Current (I _n)	1.9 A 1.8 A 0.9 A
Rated Efficiency	80 %
Rated Speed	1770 r/min
Selling Unit of Measure	piece
Service Factor	1.15
Shaft Diameter	0.63 in
Short Description	0.5 HP, 1800 RPM, Frame Size 56C, C-Face, 3 PH, TEFC, 208-230/460 V
Standards	NEMA
Starting of Motor	Direct On Line
Stocked At (Warehouses)	China Alabama, United States Alaska, United States
Type of Duty	1800 r/min Continuous
UNSPSC	26101112
Voltage Rating	208 V 230 V 460 V

Categories

Motors and Generators → NEMA Low Voltage AC Motors → Washdown Motors → Food safe stainless steel motors









