

PRODUCT-DETAILS

HTFX254040 23KV 40A FX FULL-RANGE FUSE, OUTDOO



General Information	
Extended Product Type	HTFX254040
Product ID	7TAA120700R0017
Catalog Description	23KV 40A FX FULL-RANGE FUSE, OUTDOO
Long Description	23.0kV 40 Amp FX style full range fuse

Ordering	
UPC	783786511587
Country of Origin	United States (US)
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 EA
Package Level 1 Width	0 mm 0 in
Package Level 1 Height	0 mm 0 in
Package Level 1 Depth /	0 mm

© 2024 ABB. All rights reserved.

Subject to change without notice

Length	0 in
Package Level 2 Units	4 EA
Package Level 2 Width	330.2 mm 13 in
Package Level 2 Height	127 mm 5 in
Package Level 2 Depth / Length	609.6 mm 24 in

Technical UL/CSA	
Short-Circuit Current Bating (SCCB)	50,000 A

Additional Information	
Application	Installed in Drywall Canisters for Distrbution Transformer Protection, Mounted with Spades, Externally mounted on Overhead distribution systems, Installed in Elastimold MCAN Rubber Molded Canister for Deadfront/Submersible applications, Installed directly in Oil.
Brand / Label	Hi-Tech
Current Rating	40 A
Effective Date	20061214
Material	Tin-Plated Brass Caps, Resin-Rich Filament Wound Glass/Epoxy Body
Mounting Type	Spade Mount
Product Name	In circuits of 2,300 V or more
Product Type	Full-Range Current-Limiting Fuse
Size	Diameter 2.2 in
Special Functions	Painted with Spades
Standards	ANSI/IEEE Standards.
Voltage Rating	23.0 kV

Certificates and Declarations	
Data Sheet, Technical Information	HTFX254040

Classifications	
ETIM 7	EC003507 - Medium-/high voltage fuse
ETIM 8	EC003507 - Medium-/high voltage fuse
UNSPSC	39121626
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4980 >> Medium voltage fuse

Categories

Low Voltage Products and Systems \rightarrow Installation Products \rightarrow Cable Accessories and Apparatus \rightarrow Cable Accessories

