




---

 PRODUCT-DETAILS

# 167LRT-F5230

## 15KV 200A BOLTED ELBOW W/TAP F5230




---

**General Information**

Extended Product Type	167LRT-F5230
Product ID	7TAA121180R0033
Catalog Description	15KV 200A BOLTED ELBOW W/TAP F5230
Long Description	200 Amp, 15kV, Loadbreak Bolted Elbow with Tap, Cable Insulation Diameter 0.640 inch to 0.820 inch. Bi-Metal Compression Lug, Conductor Size AWG Compressed Stranded #1/Solid 1/0 /mmSquared 42.41. Includes 02800X Bi-Metal Contact.

---

**Ordering**

UPC	783786283668
Country of Origin	United States (US)
Selling Unit of Measure	each

---

**Container Information**

Package Level 1 Units	1 EA
Package Level 1 Width	25.4 mm 1 in

Package Level 1 Height	25.4 mm 1 in
Package Level 1 Depth / Length	25.4 mm 1 in

## Additional Information

Application	15kV, 200 Amps
Brand / Label	Elastimold
Color	Black
Current Rating	200 A
Effective Date	20010518
Environmental Conditions	Fully Submersible
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Product Name	Terminals, electrical splices and electrical couplings
Product Type	Loadbreak Bolted Elbow with Tap
Size	Cable Insulation Diameter 0.640 inch to 0.820 inch.
Special Functions	Includes 02800X Bi-Metal Contact.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	15 kV

## Certificates and Declarations

Data Sheet, Technical Information	167LRT-F5230
-----------------------------------	--------------

## Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

## Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

