



PRODUCT-DETAILS

J6-622226-15L

15KV 600-200A JUNCTION - J6



General Information

Extended Product Type	J6-622226-15L
Product ID	7TAA122020R0320
Catalog Description	15KV 600-200A JUNCTION - J6
Long Description	15kV, 200/600 Amp Multipoint Junction. 6-Points, One 600 Amp Bushing Interface, Four 200 Amp Bushing Well Interfaces, One 600 Amp Bushing Interfaces, 15 kV, Standard 4 inch Spacing, Left Parking Stand Only

Ordering

UPC	75114355001
Country of Origin	United States (US)
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 EA
Package Level 1 Width	25.4 mm 1 in
Package Level 1 Height	25.4 mm 1 in

Package Level 1 Depth / Length	25.4 mm 1 in
--------------------------------	-----------------

Additional Information

Application	Suited for Subsurface, Vault or Padmount Applications and can be used for Sectionalizing, Looping, Tapping and Equipment Bypass.
Brand / Label	Elastimold
Connection Type	Push-In
Effective Date	20171115
Material	EPDM Rubber and Stainless Steel Mounting Brackets.
Mounting Type	Left Parking Stand.
Product Name	Terminals, electrical splices and electrical couplings
Product Type	Multi-Point Junction - 6 Points
Size	Overall Length 28.5 inches, Width 6.75 inches.
Special Functions	4 inch Center Spacing. Left Parking Stand.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C

Certificates and Declarations

Data Sheet, Technical Information	J6-622226-15L
-----------------------------------	---------------

Classifications

UNSPSC	26121630
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	1779 >> Cable accessories

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

